

eXP-S1110-XT PoE+ Gigabit Ethernet Extenders

10/100/1000 Industrial Temperature PoE+ Copper Extenders



- Extends 10/100/1000Base-T up to 10,000 feet (3 KM)
- Power remote PoE devices across 2-wire twisted pair or coaxial cable
- Rugged-design for harsh industrial operating environments of -40°C to 75°C (-40°F to 167°F)
- **On-board PoE power controller** for true compliance with IEEE802.3at
- High-Speed – up to 200 mbps aggregate line rate
- Transparent operation for all Ethernet protocols including 802.1Q VLAN packets and IP video compression schemes
- **Unique PD Reset feature** enables a central site to reset the **remote PoE device without a truck roll**
- Advanced features: Link Pass-Through*, Interlink Fault Feedback*, Auto-MDIX and Loopback, Plug and Play - Auto configuration of VDSL

Perle **eXP-S1110-XT PoE/PoE+ Gigabit Ethernet Extenders** transparently extend Ethernet beyond the general limits of 328ft / 100m **while providing Power over Ethernet (PoE)** to standards-based compliant devices such as IP cameras and wireless access points located in **extreme temperature environments**.

This technology enables users to transparently **extend up to four 10/100/1000 Power over Ethernet connections** across copper wiring. Use single twisted pair (CAT5/6/7), coax or any existing copper wiring previously used in alarm circuits, E1/T1 circuits, RS-232, RS-422, RS-485, CCTV and CATV applications.

At the central site, the 10/100/1000 Ethernet Extender has full PoE support and **operates as a Powered Device (PD)** under IEEE 802.3at supporting end-span and mid-span power sources (PSE). The PoE Ethernet Extender at the central site then transmits power over the copper wire to power the remote PoE Ethernet Extender and attached PD. The remote PoE Ethernet Extenders are **classified as Power Sourcing Equipment (PSE)**. While using standard UTP cables that carry Ethernet data, Perle eXP-S1110-XT PoE Ethernet Extenders **provide up to 30 watts of power** to Powered Devices (PDs). For longer distance applications the remote PoE Extender (CPE) can be powered by a local 48v adapter. **Learn more about PoE.**

Equipment found in **traffic management, oil and gas pipelines, weather tracking, industrial and outdoor applications** must function in temperatures that cannot be supported by a commercial based Ethernet Extender. With the ability to operate in **industrial grade temperatures of -40°F to +167°F (-40°C to +75°C)** along with a rugged steel casing, these simple and effective point to point Ethernet Copper Extenders are ideal to extend the distance between two industrial Ethernet devices subjected to harsh environments and severe temperatures such as PoE security cameras, and wireless access points.

Perle's advanced features such as Link Pass-Through* and Interlink Fault Feedback*, Loopback and remote PD reset*, enable Network administrators to "see everything" for more efficient troubleshooting and less on-site maintenance. These cost and time saving features, along with a lifetime warranty and free worldwide technical support, make Perle Ethernet Extenders the smart choice for IT professionals. **eXP-S1110-XT PoE Gigabit Ethernet Extenders** are also available with support for **commercial temperature ranges**.

eXP-S1110-XT PoE+ Gigabit Ethernet Extender Features

Extend Ethernet over twisted pair

Extend an Ethernet link over category 5e, 6 and 7 cabling up to 10,000 feet (3 km)

Extend Ethernet over Coaxial cable

Extend an Ethernet link over 75 ohm coaxial cable

On-board PoE Power Controller

As a fully compliant IEEE 802.3af PSE end-span device, this Ethernet Extender's PoE power controller provides compliant power provisioning and monitoring, properly sensing through signature detection whether or not the attached ethernet devices are PoE capable or not. This provides a safe connection for both PoE and Non-PoE capable devices.

Competitive PoE Ethernet Extender products operate as a simple passive power injector and will always apply power to RJ45 port pins which may result in damage if non-PoE compliant Ethernet devices are accidentally attached.

[Click here for more details](#)

Advanced Power capabilities

- ALT A/B and legacy PoE RJ45 pin selection
- Current limiting protection
- Remote PD reset

Fully compliant 802.3af PoE and 802.3at POE+ PSE

- Enable/Disable PSE power
- PD signature detection
- Over-Current Protection
- PD power classification detection (Class 0,1,2,3)

Fully Compliant 802.3af/at PoE PD

Only PoE Ethernet Extender solution that provides a Class 0 or 4 signature to PSE for proper operation with PSE equipment such as Cisco PoE switches.

Competitive PoE Ethernet extender solutions cannot be powered by Cisco PoE switches as they cannot provide the necessary PoE PD signature required by the switch. Without this, the switch will not supply power at all.

PSE Status Indicator

A multi-color LED provided presents the status of the PSE function for easy troubleshooting of power over Ethernet connections

PD Power Reset (Port 1)

Ideal for remotely resetting equipment, this configurable function performs a momentary power reset to the attached Powered Device (PD) on Port #1.

Read our **PD Reset Tech Note** for further details on this feature

Power Multiplier Selection

When used with 4-pair cable such as CAT5 on the VDSL Interlink port, an optional internal strap selection on the Ethernet Extender will provide VDSL transmission data on 1 pair and power across the 3 other pairs enabling even greater distances for power transmission to be achieved.

Broadest range of PoE devices supported

Support is included for a broad range of PD (Powered Devices)

- IEEE 802.3af, 802.3at PoE/PoE+ (Alternative A and B)
- Legacy High Capacitance PDs
- Cisco legacy VoIP phones and Wireless Access Points

High-Speed Performance

Utilizes second generation VDSL2 technology (ITU-T Recommendation G.993.). When operating under "Profile 30a", Perle Ethernet Extenders can provide an aggregate VDSL line rate capability of up to 200 mbps.

Actual distance and performance may vary depending on the type / gauge and condition of the wire used and if required, the amount of power you require across the VDSL Link

Plug and Play operation

Perle Ethernet Extenders will automatically configure your VDSL interlink connection. The CO/CPE peer association will be determined automatically by the Ethernet Extender. No need to set CO / CPE VDSL pairing.

Once a connection is made, both ends will automatically adjust relevant VDSL parameters to optimize the level of bandwidth possible across the copper link.

Link Pass-Through*

With Link Pass-Through the state of the 10/100/1000Base-T Ethernet connection is “passed through” the VDSL link to the 10/100/1000Base-T Ethernet connection on its remote peer. A managed switch on the remote end can then report the state (link up or link down) to its network management system so that any errors can be detected and recovered early.

Competitive Ethernet extenders without this feature will never detect or report any error conditions

Interlink Fault Feedback*

Similar to the Link Pass-Through feature, a loss of VDSL link will drop the 10/100/1000 Ethernet port on each end until the link recovers.

Auto-Negotiation

The Ethernet Extender supports auto negotiation on the 10/100/1000Base-T interface.

Auto-MDIX

Auto-MDIX (Automatic Medium-Dependent Interface crossover) detects the signaling on the 10/100/1000 Ethernet RJ45 interface and determines the type of cable connected (straight-through or crossover) and automatically adopts a compatible pinout.

Fixed Speed and Duplex

Some Ethernet equipment require a fixed speed and duplex be used or cannot auto-negotiate. By disabling Auto-Negotiation on the Ethernet Extender, a fixed speed of 10 or 100 mbps as well as Full or half Duplex can be configured through DIP switches.

VLAN

Transparent to tagged VLAN (802.1Q) packets.

Transparent to IP Video compression protocols

Fully transparent to such IP video compression schemes such as MPEG-4, H.264 and MJPEG.

Power Strain Relief strap

A strain relief strap is provided to ensure a solid and secure power connection to the Ethernet Extender. Ideal for areas that may be exposed to vibration.

Loopback

When enabled, will perform a loopback on the copper VDSL Interlink.

*Available on 1 port models.


Specifications

Lifetime limited warranty	Reach, RoHS and WEEE Compliant	HTSUS Number: 8517.62.0020	UNSPSC Code: 43222608	ECCN: 5A991
----------------------------------	---------------------------------------	--------------------------------------	---------------------------------	-----------------------



Remote (Power over Ethernet)

Local (power over link - VDSL)

Power				
Unit Powered by	eXP-1S1110PE-XT Local power adapter or VDSL	eXP-4S1110PE-XT Local power adapter or VDSL	eXP-1S1110L-XT <ul style="list-style-type: none"> Local power adapter or PoE Power Sourcing Equipment such as a Cisco PoE+ Switch on port #1 PoE+ power injector 	eXP-4S1110L-XT <ul style="list-style-type: none"> Local power adapter or PoE Power Sourcing Equipment such as a Cisco PoE+ Switch on port #1 PoE+ power injector
Provides Power to:	eXP-1S1110PE-XT Ethernet	eXP-4S1110PE-XT Ethernet	eXP-1S1110L-XT Link (VDSL Interlink)	eXP-4S1110L-XT Link (VDSL Interlink)
Power adapter connector	Barrel or terminal block			
Input Voltage Range from adapter	eXP-1S1110PE-XT 46V to 57	eXP-4S1110PE-XT 46V to 57	eXP-1S1110L-XT 29 to 57	eXP-4S1110L-XT 29 to 57
Input Voltage Range from VDSL (parasitic)	eXP-1S1110PE-XT 24 to 57	eXP-4S1110PE-XT 24 to 57	eXP-1S1110L-XT N/A	eXP-4S1110L-XT N/A
Power Connectors	5.5mm x 9.5mm x 2.1mm barrel socket and 2 pin terminal Block			
				

	Remote (Power over Ethernet)		Local (power over link - VDSL)	
Ethernet				
10/100/1000Base-T Port(s)	eXP-1S1110PE-XT 1 port RJ45 Shielded	eXP-4S1110PE-XT 4 port RJ45 Shielded	eXP-1S1110L-XT 1 port RJ45 Shielded	eXP-1S1110L-XT 4 port RJ45 Shielded
Auto-MDIX	Auto-MDIX enables proper operation with either straight-through or crossover cabling			
Distance	Distance up to 100 meters (328 feet) as per IEEE 802.3			
Maximum Frame Size	1522			
Type of PoE device	eXP-1S1110PE-XT PSE (PoE / PoE+) IEEE 802.3af/at	eXP-4S1110PE-XT PSE (PoE / PoE+) IEEE 802.3af/at	eXP-1S1110L-XT PD (Class 0 or 4 device)	eXP-4S1110L-XT PD (Class 0 or 4 device)
PoE PSE Power Budget	eXP-1S1110PE-XT Refer to the Power Reach Installation Planning Guide	eXP-4S1110PE-XT Refer to the Power Reach Installation Planning Guide	eXP-1S1110L-XT N/A	eXP-4S1110L-XT N/A

PoE PSE RJ45 Cable Pinout	<div>eXP-1S1110PE-XT<ul style="list-style-type: none">Alternative A (default) on all ports Pins 3,6 Neg, Pins 1,2 PosAlternative B: selectable on port #1 Pins 7,8 Neg, Pins 4,5 PosLegacy Cisco Pre-Standard: selectable on port #1 Pins 7,8 Pos, Pins 4,5 Neg</div>	<div>eXP-4S1110PE-XT<ul style="list-style-type: none">Alternative A (default) on all ports Pins 3,6 Neg, Pins 1,2 PosAlternative B: selectable on port #1 Pins 7,8 Neg, Pins 4,5 PosLegacy Cisco Pre-Standard: selectable on port #1 Pins 7,8 Pos, Pins 4,5 Neg</div>	<div>eXP-1S1110L-XTN/A</div>	<div>eXP-4S1110L-XTN/A</div>
	Remote (Power over Ethernet)		Local (power over link - VDSL)	
VDSL – Interlink				
RJ45, BNC, Terminal Block	<div>Ethernet Extenders must be connected in pairs using unconditioned wire. Circuits that run through signal equalization equipment are not permitted. TIP and RING are polarity insensitive. Surge suppression of 400 volts between TIP and RING. Choice of RJ45, BNC or terminal block models for VDSL link connector:</div> <ul style="list-style-type: none">RJ45 – RING pin 4, TIP pin 5 (TIA 568 A/B)BNC – Coaxial 50 and 75 ohm cable with BNC connectorTerminal Block – 2 position screw connectors for use with twisted pair telephone, alarm or serial cabling between 19 (0.9 mm) and 26 AWG (0.44 mm).			

Power Injection over the Interlink (VDSL) – 2-wire	eXP-1S1110PE-XT N/A	eXP-4S1110PE-XT N/A	eXP-1S1110L-XT Injects SELV compliant voltage and VDSL data across a single pair of cooper wires (pins 4 and 5) or 2 conductor BNC coaxial cable	eXP-4S1110L-XT Injects SELV compliant voltage and VDSL data across a single pair of cooper wires (pins 4 and 5) or 2 conductor BNC coaxial cable
Short Circuit Protection	eXP-1S1110PE-XT N/A	eXP-4S1110PE-XT N/A	eXP-1S1110L-XT Short Circuit protection provided	eXP-4S1110L-XT Short Circuit protection provided
Reverse Polarity Protection	eXP-1S1110PE-XT The voltage from the VDSL link requires proper polarity in order to provide power to the remote extender. Reverse polarity protection however will ensure that there is no damage to the extender	eXP-4S1110PE-XT The voltage from the VDSL link requires proper polarity in order to provide power to the remote extender. Reverse polarity protection however will ensure that there is no damage to the extender	eXP-1S1110L-XT N/A	eXP-4S1110L-XT N/A

Power Multiplier Selection	When used with 4-pair cable such as CAT5 on the VDSL Interlink port, an optional internal strap selection on the Ethernet Extender will provide VDSL transmission data on 1 pair and power across the 3 other pairs enabling even greater distances for power transmission to be achieved
----------------------------	---

VDSL2 Line Rate/Reach

Actual distance and rates experienced will depend on condition and gauge of wire used. This Rate/Reach table applies to 24 AWG (0.5 MM) twisted pair wiring on RJ45 (RJ) and terminal block (TB) models

High Speed Asymmetric

Reach (Distance)		VDSL Rate (Mbps)	
feet	meters	Downstream	Upstream
500	152	101	92
1000	305	101	63
1500	457	90	38
2000	610	62	24
2500	762	55	10
3000	914	42	5
3500	1000	35	3

High Speed Symmetric

Reach (Distance)		VDSL Rate (Mbps)	
feet	meters	Downstream	Upstream
500	152	101	101
1000	305	85	101
1500	457	62	47
2000	610	60	29
2500	762	44	14
3000	914	30	7
3500	1000	29	4


Long Reach Symmetric

Reach (Distance)		VDSL Rate (Mbps)	
feet	meters	Downstream	Upstream
500	152	53	44
1000	305	53	43
2500	762	39	18
4000	1219	25	4
5500	1676	17	1.9
7000	2134	8	2.3
7500	2286	7	2.2
8000	2438	5	2.2
Long Reach Asymmetric			
Reach (Distance)		VDSL Rate (Mbps)	
feet	meters	Downstream	Upstream
500	152	78	16
1000	305	78	16
2500	762	55	10
4000	1219	31	0.8
5500	1676	20	0.6
7000	2134	11	0.6
7500	2286	10	0.6
8000	2438	8	0.6

This table applies when the power multiplier option is selected

Power Budget	<p>The amount of available power at the PoE/PoE+ PD is dependent on the scenario planned.</p> <p>Refer to the Power Reach Installation Planning Guide</p>
Indicators	
Power / TST	<p>This green LED is turned on when power is applied to the Ethernet Extender. Otherwise it is off. The LED will blink when in Loopback test mode.</p>
CO - Local	<p>Ethernet Extender is operating in CO VDSL mode</p>
CPE - remote	<p>Ethernet Extender is operating in CPE VDSL mode</p>
ILNK	<p>Indicates Link Status and activity on the Interlink (VDSL) port</p>
ETH	<p>Indicates link status and activity on Ethernet port(s).</p>
	<p>Remote (Power over Ethernet) Local (power over link - VDSL)</p>

PSE Status	eXP-1S1110PE-XT	eXP-4S1110PE-XT	eXP-1S1110L-XT	eXP-4S1110L-XT
	<p>This LED will signify the status of the PSE function. Using multi-color and blinking the unit will show the following status for the PSE;</p> <p>GREEN — Solid: The PSE has successfully detected a compliant PD and is applying power over the UTP (for legacy pin out simply show active power when applied)</p> <p>YELLOW — Solid: The PSE is not active. This means the PSE has been configured to provide power, but the PD is :</p> <ul style="list-style-type: none"> • Not connected • Has not detected a compliant PD and is not applying power • PSE has turned off 	<p>This LED will signify the status of the PSE function. Using multi-color and blinking the unit will show the following status for the PSE;</p> <p>GREEN — Solid: The PSE has successfully detected a compliant PD and is applying power over the UTP (for legacy pin out simply show active power when applied)</p> <p>YELLOW — Solid: The PSE is not active. This means the PSE has been configured to provide power, but the PD is :</p> <ul style="list-style-type: none"> • Not connected • Has not detected a compliant PD and is not applying power • PSE has turned off 	N/A	N/A

	<p>power for Reset function</p> <p>power for Reset function</p> <p>OFF — PSE function switch disabled</p> <p>OFF — PSE function switch disabled</p> <p>RED — Blinking: Error Conditions</p> <p>RED — Blinking: Error Conditions</p> <ul style="list-style-type: none"> • Capacitance too High — 1 blink • Resistance too Low or short circuit — 2 blinks • Resistance too high or open circuit — 3 blinks • Capacitance too High — 1 blink • Resistance too Low or short circuit — 2 blinks • Resistance too high or open circuit — 3 blinks
Switches	
Access	Switch settings are accessible through a side opening in the chassis
	
Rate/Reach	Two switches enable the user to select the right balance between speed and distance for their environment.
Signal to Noise Ratio	Selectable Signal to Noise Ratio (SNR) of 6dB or 9dB. The higher SNR number provides better impulse noise protection but lowers performance.
Auto-Negotiation (802.3u) control on Port 1	<ul style="list-style-type: none"> • <i>Enabled (Default)</i> - The Ethernet Extender uses 802.3u Auto-negotiation on the 10/100/1000Base-T interface. It is set to advertise full duplex. • <i>Disabled</i> - The Ethernet Extender sets the port according to the position of the speed and duplex switches.

Force Ethernet Speed on Port 1	<p>When Auto-Negotiation switch is disabled, a fixed speed can be forced on port 1</p> <ul style="list-style-type: none"> • 100 (Default) • 10
Force Ethernet Duplex on Port 1	<p>When Auto-Negotiation switch is disabled, Full or half Duplex can be forced on port 1</p> <ul style="list-style-type: none"> • Full (Default) • Half
Link Mode	<ul style="list-style-type: none"> • <i>Standard (Default)</i> - The 10/100/1000Base-T link remains active independent of the state of the Ethernet link on its remote peer. • <i>Link Pass-Through</i> - the state of the 10/100/1000Base-T Ethernet connection is “passed through” or propagated across the VDSL link to the 10/100/1000Base-T Ethernet link on its remote Ethernet Extender peer.
Interlink Fault Feedback	<ul style="list-style-type: none"> • <i>Enabled</i> – A loss of VDSL link will drop the 10/100/1000 Ethernet port on each end until the link recovers • <i>Disabled (Default)</i> - The state of the VDSL link is not propagated to the 10/100/1000Base-T port
Loopback	<ul style="list-style-type: none"> • <i>Enabled</i> – The VDSL interlink will perform a loopback function, retransmitting all received Ethernet frames back to its remote peer. • <i>Disabled (Default - Up)</i>
	<p>Remote (Power over Ethernet) Local (power over link - VDSL)</p>

PoE PD Class selection	eXP-1S1110PE-XT N/A	eXP-4S1110PE-XT N/A	eXP-1S1110L-XT (Internal strap) for PoE PD classification type identification for attached IEEE 802.3at compliant PoE+ switch on port #1 Class 0 – PoE PD device - 0.44-12.94W (Default) Class 4 – PoE+ PD device 12.95 – 25.5W	eXP-4S1110L-XT (Internal strap) for PoE PD classification type identification for attached IEEE 802.3at compliant PoE+ switch on port #1 Class 0 – PoE PD device - 0.44-12.94W (Default) Class 4 – PoE+ PD device 12.95 – 25.5W
------------------------	-------------------------------	-------------------------------	---	---

PD Reset (Port 1)	eXP-1S1110PE-XT When enabled (down), the Ethernet Extender will upon loss of link on the VDSL Interlink port, turn off PSE output power to the PD device for 2 seconds then turn the power back on. The power remains on until the VDSL link transitions from up to down again. When PD Power Reset is disabled (default), loss of VDSL link has no effect on power supplied to the PD.	eXP-4S1110PE-XT When enabled (down), the Ethernet Extender will upon loss of link on the VDSL Interlink port, turn off PSE output power to the PD device for 2 seconds then turn the power back on. The power remains on until the VDSL link transitions from up to down again. When PD Power Reset is disabled (default), loss of VDSL link has no effect on power supplied to the PD.	eXP-1S1110L-XT N/A	eXP-4S1110L-XT N/A
Environmental Specifications				
Operating Temperature	-40°C to 75°C (-40°F to 167°F)			
Storage Temperature	-40°C to 75°C (-40°F to 167°F)			
Operating Humidity	5% to 90% non-condensing			
Storage Humidity	5% to 95% non-condensing			

Operating Altitude	Up to 3,048 meters (10,000 feet)			
	Remote (Power over Ethernet)		Local (power over link - VDSL)	
Current mA	eXP-1S1110PE-XT 114 @ 56vdc	eXP-4S1110PE-XT 163 @ 56vdc	eXP-1S1110L-XT 144 @ 48vdc	eXP-4S1110L-XT 200 @ 48vdc
Unit Power Consumption watts	eXP-1S1110PE-XT 6.4	eXP-4S1110PE-XT 9.1	eXP-1S1110L-XT 6.9	eXP-4S1110L-XT 9.6
Heat Output (BTU/HR)	eXP-1S1110PE-XT 21.84	eXP-4S1110PE-XT 31.05	eXP-1S1110L-XT 23.54	eXP-4S1110L-XT 32.76
MTBF with power adapter (Hours)*	N/A			
MTBF without power adapter (Hours)*	eXP-1S1110PE-XT 300,172 Hours	eXP-4S1110PE-XT 262,530 Hours	eXP-1S1110L-XT 339,780 Hours	eXP-4S1110L-XT 294,389 Hours
	Calculation model based on MIL-HDBK-217-FN2 @ 30°C			
Mounting				
Wall/Desk	Standard			
Din Rail Kit	Optional			
Rack Mount Kit	Optional			
	Remote (Power over Ethernet)		Local (power over link - VDSL)	
Product Weight and Dimensions				
Weight	eXP-1S1110PE-XT 0.58 Kg, 1.3 lbs	eXP-4S1110PE-XT 0.61Kg, 1.34 lbs	eXP-1S1110L-XT 0.58 Kg, 1.3 lbs	eXP-4S1110L-XT 0.61Kg, 1.34 lbs

Dimensions	163 x 116 x 37 mm, 6.4 x 4.6 x 1.46 inches			
	Remote (Power over Ethernet)		Local (power over link - VDSL)	
Packaging				
Shipping Weight	eXP-1S1110PE-XT 0.79 Kg, 1.7 lbs	eXP-4S1110PE-XT 0.82 Kg 1.8 lbs	eXP-1S1110L-XT 0.79 Kg, 1.7 lbs	eXP-4S1110L-XT 0.82 Kg 1.8 lbs
Shipping Dimensions	20 x 30 x 7 cm, 7.9 x 11.8 x 2.8 inches			
Regulatory Approvals				
Emissions	<ul style="list-style-type: none">• CISPR 32:2015/EN 55032:2015 (Class A)• IEC/EN 61000-3-2• IEC/EN 61000-3-3			
Immunity	<ul style="list-style-type: none">• CISPR 35/EN 55035• IEC/EN 61000-4-2• IEC/EN 61000-4-3• IEC/EN 61000-4-4• IEC/EN 61000-4-5• IEC/EN 61000-4-6• IEC/EN 61000-4-8• IEC/EN 61000-4-11			
Electrical Safety	<ul style="list-style-type: none">• UL/EN/IEC 62368-1• CAN/CSA C22.2 No. 62368-1• UL 60950-1• IEC 60950-1(ed 2); am1, am2• EN 60950-1:2006+A11:2009+A1:2010+A12:2011+A2:2013• CSA C22.2 No. 60950-1			

Product List



eXP-1S1110L-RJ-XT - Gigabit Ethernet Industrial Temperature PoE Ethernet Extender - Provides power over VDSL Link. 1 port 10/100/1000Base-T (RJ-45). RJ45 Interlink (VDSL2) connector.

Power Cord & Part Number(s)

None

06004310



eXP-1S1110PE-RJ-XT - Gigabit Ethernet Industrial Temperature PoE+ Ethernet Extender - Provides power over Ethernet as a PSE. 1 port 10/100/1000Base-T (RJ-45). RJ45 Interlink (VDSL2) connector.

Power Cord & Part Number(s)

None

06004790



eXP-1S1110L-BNC-XT - Gigabit Ethernet Industrial Temperature PoE Ethernet Extender - Provides power over VDSL Link. 1 port 10/100/1000Base-T (RJ-45). BNC Interlink (VDSL2) connector.

Power Cord & Part Number(s)

None

06004320



eXP-1S1110PE-BNC-XT - Gigabit Ethernet Industrial Temperature PoE+ Ethernet Extender - Provides power over Ethernet as a PSE. 1 port 10/100/1000Base-T (RJ-45). BNC Interlink (VDSL2) connector.

Power Cord & Part Number(s)

None

06004800



eXP-1S1110L-TB-XT - Gigabit Ethernet Industrial Temperature PoE Ethernet Extender - Provides power over VDSL Link. 1 port 10/100/1000Base-T (RJ-45). Terminal Block Interlink (VDSL2) connector.

Power Cord & Part Number(s)

None

06004330



eXP-1S1110PE-TB-XT - Gigabit Ethernet Industrial Temperature PoE+ Ethernet Extender - Provides power over Ethernet as a PSE. 1 port 10/100/1000Base-T (RJ-45). Terminal Block Interlink (VDSL2) connector.

Power Cord & Part Number(s)

None

06004810



eXP-4S1110PE-RJ-XT - Gigabit Ethernet Industrial Temperature PoE+ Ethernet Extender - Provides power over Ethernet as a PSE. 4 port 10/100/1000Base-T (RJ-45). RJ45 Interlink (VDSL2) connector.

Power Cord & Part Number(s)

None

06004910



eXP-4S1110PE-BNC-XT - Gigabit Ethernet Industrial Temperature PoE+ Ethernet Extender - Provides power over Ethernet as a PSE. 4 port 10/100/1000Base-T (RJ-45). BNC Interlink (VDSL2) connector.

Power Cord & Part Number(s)

None

06004920



eXP-4S1110PE-TB-XT - Gigabit Ethernet Industrial Temperature PoE+ Ethernet Extender - Provides power over Ethernet as a PSE. 4 port 10/100/1000Base-T (RJ-45). Terminal Block Interlink (VDSL2) connector.

Power Cord & Part Number(s)

None

06004930

Related Accessories

Accessories



DIN Rail Mounting Kit for 4 & 8 port IOLAN desktop models, all Stand-Alone Media Converters and all Stand-alone Ethernet Extenders. Two of these brackets are required for the 8 port STS8-D model.

04030840



Standalone media converter wall / rack mount bracket

05059999