




## Product information BAT-Controller WLC25

Industrial Ethernet:Industrial Wireless LAN:Chassis:BAT-Management:BAT-Controller WLC25

<http://e-catalog.hirschmann.com/link/57078-24455-49859-24497-118024-144719/en/conf/ui/istate>

|  |   |
|--|---|
| Name                                     | BAT-Controller WLC25  |
|  |    |
|  | Central Firmware deployment and management of the Access Points. Requires an external web server.   |
| <b>Delivery informations</b>             |   |
| Availability                             | available   |
| <b>Product description</b>               |   |
| Description                              | Central Firmware deployment and management of the Access Points. Requires an external web server.   |
| Port type and quantity                   | 4 individual Ethernet ports 10/100/1000 Mbps  |
| Type                                     | BAT-Controller WLC25  |
| Order No.                                | 942 034-001   |
| Managed Access Points                    | 25  |
| <b>More Interfaces</b>                   |   |
| Power supply/signaling contact           | Internal power supply unit (110–230 V, 50-60 Hz)  |
| <b>Hardware requirements</b>             |   |
| Network                                  | BAT54 and BAT300 access points  |
| <b>Mechanical construction</b>           |   |
| Housing                                  | Robust metal housing, 19" 1 HU, with removable mounting brackets, network connectors on the front   |
| <b>Ambient conditions</b>                |   |
| Operating temperature                    | 5 °C ... 40 °C  |
| Relative humidity (non-condensing)       | 0 % ... 95 %  |
| Dimensions (W x H x D)                   | 435 x 45 x 207 mm   |
| Weight                                   | 3800 g  |
| <b>Scope of delivery and accessories</b> |   |
| Scope of delivery                        | CD including firmware, management software (LANconfig, LANmonitor, WLANmonitor) and documentation. Printed Installation Guide. 1 serial configuration cable (1.5 m), 1 Ethernet cable, 1 Cable IEC power cord (3 m), return voucher, 19 Inch DIN rail adapter |

For more information please contact:

**Hirschmann Automation and Control GmbH**

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: [inet-sales@belden.com](mailto:inet-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect.

