




Product information M-FAST SFP-TX/RJ45 - M-FAST SFP-TX/RJ45

Industrial Ethernet: System Accessories: Fiberoptic Transceiver: SFP Fast-Ethernet Transceiver for media module: M-FAST SFP-TX/RJ45

<http://e-catalog.hirschmann.com/link/57078-24455-24544-24535-24528-373355/en/conf/uisstate>

Name	M-FAST SFP-TX/RJ45
	
	SFP TX Fast Ethernet Transceiver for Switch RSP only port 1/2 and PRP (Parallel Redundancy Protocol), 100 Mbit/s full duplex auto neg. fixed, cable crossing not supported
Delivery informations	
Availability	available
Product description	
Description	SFP TX Fast Ethernet Transceiver for Switch RSP only port 1/2 and PRP (Parallel Redundancy Protocol), 100 Mbit/s full duplex auto neg. fixed, cable crossing not supported
Port type and quantity	1 x 100BASE-T with RJ45-socket
Type	M-FAST SFP-TX/RJ45
Order No.	942 098-001
Replaced by	M-FAST SFP-TX/RJ45 EEC
Network size - length of cable	
Twisted pair (TP)	0 m ... 100 m
Power requirements	
Operating voltage	power supply via the switch
Power consumption	1 W
Ambient conditions	
Operating temperature	0 °C ... +60 °C
Storage/transport temperature	-40°C ... +85°C
Relative humidity (non-condensing)	10% ... 95%
MTBF	67 years (Telcordia GR-468-CORE)
Mechanical construction	
Dimensions (W x H x D)	14 mm x 14 mm x 70 mm
Mounting	SFP slot
Weight	40 g
Protection class	IP 20
Mechanical stability	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz - 13.2 Hz, 90 min. 0.7g, 13.2 Hz - 100 Hz, 90 min. 3.5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min. 1g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min.
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz - 150 kHz), 10 V (150 kHz - 80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC CFR47 Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of information technology equipment	cUL 60950-1
Scope of delivery and accessories	
Scope of delivery	SFP module



HIRSCHMANN

A **BELDEN** BRAND

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.