



Product information OZD Modbus Plus G12

Fiber Interfaces:Fieldbus Repeater:Modbus Plus LWL-Repeater:OZD Modbus Plus G12

<https://www.e-catalog.beldensolutions.com:443/link/57078-57141-57128-57133-501160/en/conf/uisstate>

Name	OZD Modbus Plus G12
	
	New generation: interface converter electrical/optical for Modbus Plus-field bus networks; repeater function; for quartz glass und PCF (HCS) FO
Delivery informations	
Availability	available
Product description	
Description	New generation: interface converter electrical/optical for Modbus Plus-field bus networks; repeater function; for quartz glass und PCF (HCS) FO
Port type and quantity	2 x optical: 4 sockets BFOC 2.5 (STR); 1 x electrical: Sub-D 9-pin, female, pin assignment according to Modbus Plus-Standard
Type	OZD Modbus Plus G12
Order No.	942 148-010
Electrical interface	
Signal type	Modbus Plus
Bit rate	1 Mbit/s
Signal delay time (optional input/output)	<1 µs
Input/output signal	Modbus Plus Bus
Length of Modbus cable	100 m
Connection capability	max. 31 terminal devices
Terminator	external
Galvanic isolation	shielding/housing: no; data lines/housing: yes
Optical interface	
Wavelength	860 nm
Cascadability	not limited
More Interfaces	
Power supply	8-pin terminal block, screw mounting
Signaling contact	8-pin terminal block, screw mounting
Network size - length of cable	
Single mode fiber (SM) 9/125 µm	-
Multimode fiber (MM) 50/125 µm	2300 m 10 dB link budget at 860 nm; A = 3 dB/km, 3 dB reserve
Multimode fiber (MM) 62.5/125 µm	2300 m 11 dB link budget at 860 nm; A = 3.5 dB/km, 3 dB reserve
Multimode fiber HCS (MM) 200/230 µm	1500 m 16 dB link budget at 860 nm; A = 8 dB/km, 3 dB reserve
Power requirements	
Operating voltage	24 VDC (18 ... 32 VDC), reverse polarity protected, safety extra-low voltage
Current consumption	160 mA
Power consumption	3.9 W
Redundancy	
Redundancy functions	HIPER-Ring (ring structure), redundant 24 V infeed
Ambient conditions	
Operating temperature	0 °C to +60 °C
Storage/transport temperature	-40 °C to +70 °C
Relative humidity	<95% (non-condensing)
Mechanical construction	
Dimensions (W x H x D)	40 x 111 x 73.5 mm
Mounting	DIN rail or mounting plate
Weight	620 g

Fiber Interfaces:Fieldbus Repeater:Modbus Plus LWL-Repeater:OZD Modbus Plus G12

<https://www.e-catalog.beldensolutions.com:443/link/57078-57141-57128-57133-501160/en/conf/ui/state>

Protection class	IP 40
Housing material	die-cast zink
Approvals	
Basis Standard	CE
Scope of delivery and accessories	
Scope of delivery	device, start-up instructions
Accessories to order separately	manual

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.