



HIRSCHMANN

A BELDEN BRAND

Product information OZD Profi 12M G22 EEC

Fiber Interfaces:Fieldbus Repeater:Profibus LWL-Repeater:OZD Profi 12M G22 EEC

<https://www.e-catalog.beldensolutions.com:443/link/57078-57141-57128-57129-500572/en/conf/uistate>

Name		OZD Profi 12M G22 EEC
		
		New generation: interface converter electrical/optical for PROFIBUS-field bus networks; repeater function; for quartz glass F0; approval for Ex-zone 2; (Class 1, Div. 2); extended temperature and humidity range
Delivery informations		
Availability		available
Product description		
Description		New generation: interface converter electrical/optical for PROFIBUS-field bus networks; repeater function; for quartz glass F0; approval for Ex-zone 2; (Class 1, Div. 2); extended temperature and humidity range
Port type and quantity		2 x optical: 4 sockets BFOC 2.5 (STR) 2 x electrical: Sub-D 9-pin, female, pin assignment according to EN 50170 part 1
Type		OZD Profi 12M G22 EEC
Order No.		942 148-103
Electrical interface		
Signal type		PROFIBUS (DP-V0, DP-V1, DP-V2 und FMS)
Bit rate		9.6; 19.2; 45.45; 93.75; 187.5; 500 kbit/s; 1.5; 3; 6; 12 Mbit/s (automatic setting)
Signal delay time (optional input/output)		<= 6.5 bit times
Input/output signal		RS 485 level
Input voltage range		-7 V ... +12 V
Galvanic isolation		yes
Optical interface		
Wavelength		860 nm
Cascadability		not limited
More interfaces		
Power supply		8-pin terminal block, screw mounting
Signaling contact		8-pin terminal block, screw mounting
Measuring outputs "Optical input power"		8-pin terminal block, screw mounting
Network size - length of cable		
Single mode fiber (SM) 9/125 µm		-
Multimode fiber (MM) 50/125 µm		3000 m 13 dB link budget at 860 nm A = 3 dB/km, 3 dB reserve
Multimode fiber (MM) 62.5/125 µm		3000 m 15 dB link budget at 860 nm A = 3.5 dB/km, 3 dB reserve
Multimode fiber HCS (MM) 200/230 µm		1000 m 18 dB link budget at 860 nm A = 8 dB/km, 3 dB reserve
Multimode fiber POF (MM) 980/1000 µm		-
Power requirements		
Operating voltage		18 ... 32 VDC, typ. 24 VDC
Galvanic isolation		yes
Current consumption		max. 190 mA
Power consumption		4.5 W
Output voltage/output current (pin6)		5 VDC +5%, -10%, short circuit-proof/10 mA
Redundancy		
Redundancy functions		HIPER-Ring (ring structure), redundant 24 V infeed
Ambient conditions		
Operating temperature		-20 °C to +60 °C
Storage/transport temperature		-40 °C to +70 °C
Relative humidity		100% (condensing)
Mechanical construction		
Dimensions (W x H x D)		40 x 140 x 77.5 mm



HIRSCHMANN

A Belden Brand

Fiber Interfaces:Fieldbus Repeater:Profibus LWL-Repeater:OZD Profi 12M G22 EEC

<https://www.e-catalog.beldensolutions.com:443/link/57078-57141-57128-57129-500572/en/conf/ui/state>

Mounting	DIN rail or mounting plate
Weight	500 g
Protection class	IP 40
Housing material	die-cast zinc
Approvals	
Basis Standard	CE, FCC
Safety of industrial control equipment	cUL61010
Scope of delivery and accessories	
Scope of delivery	device, start-up instructions

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.