




Product information Compact OpenRail Gigabit Ethernet Switch 8-24 ports - RS30-2402T1T1SDAEHH08.0.

Industrial Ethernet: Compact configurable managed switches: with Firmware Release 8: Compact OpenRail Gigabit Ethernet Switch 8-24 ports

<http://e-catalog.hirschmann.com/link/57078-24455-49854-374156-373458/en/RS30-2402T1T1SDAEHH08.0/uistate>

| | |
|--|---|
| Name | Compact OpenRail Gigabit Ethernet Switch 8-24 ports |
| |  |
| | 26 port Gigabit/Fast-Ethernet-Switch (2 x Gigabit Ethernet, 24 x Fast Ethernet), managed, software Layer 2 Enhanced, for DIN rail store-and-forward-switching, fanless design |
| Delivery informations | |
| Availability | available |
| Product description | |
| Description | 26 port Gigabit/Fast-Ethernet-Switch (2 x Gigabit Ethernet, 24 x Fast Ethernet), managed, software Layer 2 Enhanced, for DIN rail store-and-forward-switching, fanless design |
| Port type and quantity | 26 Ports in total, 2 Gigabit Ethernet ports; 1. uplink: 10/100/1000BASE-TX, RJ45; 2. uplink: 10/100/1000BASE-TX, RJ45; 24 x standard 10/100 BASE TX, RJ45 |
| Type | RS30-2402T1T1SDAEHH08.0. |
| Order No. | 943 434-037 |
| More Interfaces | |
| Power supply/signaling contact | 1 x plug-in terminal block, 6-pin |
| V.24 interface | 1 x RJ11 socket |
| USB interface | 1 x USB to connect the AutoConfiguration Adapter ACA21-USB |
| Network size - length of cable | |
| Twisted pair (TP) | 0 m ... 100 m |
| Network size - cascadiability | |
| Line - / star topology | any |
| Ring structure (HIPER-Ring) quantity switches | 50 (reconfiguration time < 0.3 sec.) |
| Power requirements | |
| Operating voltage | 12/24/48 V DC (9,6-60) V and 24 V AC (18-30) V (redundant) |
| Current consumption at 24 V DC | 654 mA |
| Current consumption at 48 V DC | 327 mA |
| Power output in Btu (IT) h | 53.6 |
| Software | |
| Management | Serial interface, web interface, SNMP V1/V2, HiVision file transfer SW HTTP/TFTP |
| Diagnostics | LEDs, log-file, relay contact, RMON, port mirroring 1:1, topology discovery 802.1AB, address conflict detection, network error detection, SFP diagnostic (temperature, optical input and output power (µW and dBm)), Trap for configuration saving and changing, duplex mismatch detection, disable learning. |
| Configuration | Comand line interface (CLI), TELNET, BootP, DHCP, DHCP option 82, HiDiscovery, easy device exchange with auto-configuration adapter ACA21-USB (automatic software and/or configuration upload), automatic invalid configuration undo, configuration signature (water marking) |
| Security | Port Security (IP und MAC) with multiple addresses, SNMP V3 (no encryption) |
| Redundancy functions | HIPER-ring (ring structure), MRP (IEC-ring functionality), RSTP 802.1D-2004, redundant network/ring coupling, MRP and RSTP in parallel, redundant 24 V power supply |
| Filter | QoS 4 classes, port prioritisation (IEEE 802.1D/p), VLAN (IEEE 802.1Q), shared VLAN learning, multicast (IGMP Snooping/Querier), multicast detection unknown multicast, broadcastlimiter, fast aging |
| Industrial Profiles | EtherNet/IP and PROFINET (2.2 PDEV, GSDML stand-alone generator, automatic device exchange) profiles included, configuration and diagnostic via automation software tools like e.g. STEP7, or Control Logix |
| Time synchronisation | SNTP client/server, PTP / IEEE 1588 |
| Flow control | Flow control 802.3x, port priority 802.1D/p, priority (TOS/DIFFSERV) |
| Presettings | Standard |
| Ambient conditions | |
| Operating temperature | 0 °C ... 60 °C |
| Storage/transport temperature | -40 °C ... 70 °C |



Industrial Ethernet: Compact configurable managed switches: with Firmware Release 8: Compact OpenRail Gigabit Ethernet Switch 8-24 ports

<http://e-catalog.hirschmann.com/link/57078-24455-49854-374156-373458/en/RS30-2402T1T1SDAEHH08.0/uisstate>

| | |
|--|---|
| Relative humidity (non-condensing) | 10 % ... 95 % |
| MTBF | 33.5 years (MIL-HDBK-217F) |
| Protective paint on PCB | No |
| Mechanical construction | |
| Dimensions (W x H x D) | 110 mm x 131 mm x 111 mm |
| Mounting | DIN Rail |
| Weight | 600 g |
| Protection class | IP20 |
| Mechanical stability | |
| IEC 60068-2-27 shock | 15 g, 11 ms duration, 18 shocks |
| IEC 60068-2-6 vibration | 1 mm, 2 Hz-13.2 Hz, 90 min.; 0.7 g, 13.2 Hz-100 Hz, 90 min.; 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min.; 1 g, 9 Hz-150 Hz, 10 cycles, 1 octave/min |
| EMC interference immunity | |
| EN 61000-4-2 electrostatic discharge (ESD) | 6 kV contact discharge, 8 kV air discharge |
| EN 61000-4-3 electromagnetic field | 10 V/m (80-1000 MHz) |
| EN 61000-4-4 fast transients (burst) | 2 kV power line, 1 kV data line |
| EN 61000-4-5 surge voltage | power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line |
| EN 61000-4-6 conducted immunity | 3 V (10 kHz-150 kHz), 10 V (150 kHz-80 MHz) |
| EMC emitted immunity | |
| FCC CFR47 Part 15 | FCC 47 CFR Part 15 Class A |
| EN 55022 | EN 55022 Class A |
| Approvals | |
| Safety of industrial control equipment | cUL 508 |
| Hazardous locations | ISA 12.12.01 Class 1 Div. 2 |
| Shipbuilding | n/a |
| Railway norm | n/a |
| Substation | n/a |
| Scope of delivery and accessories | |
| Scope of delivery | Device, terminal block, operating manual |

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.