


## Product information ACA11-EEC

Industrial Ethernet:System Accessories:Adapter cable:ACA11-EEC

Name	ACA11-EEC
	The ACA 11 auto-configuration adapter saves the configuration data of the connected switch. It enables managed switched to be easily commissioned and
Dallares Information	quickly replaced. The ACA 11 is supported by the following Switch families: RS20, RS30, RS40, MS20, MS30
Delivery informations	
Availability	available
Product description	The ACA 11 are a self-counting above to the self-counting date of the country of the Hamiltonian and a self-counting date of the country of the self-country of the se
Description	The ACA 11 auto-configuration adapter saves the configuration data of the connected switch. It enables managed switched to be easily commissioned and
Tyrno	quickly replaced. The ACA 11 is supported by the following Switch families: RS20, RS30, RS40, MS20, MS30  ACA11-EEC
Type Order No.	
More Interfaces	943 751-002
To the RS232 interface on the switch	RJ11 connector
To the RS232 interface on the PC or notebook	n/a
To the USB interface on the switch	n/a
Power requirements	100
Operating voltage	via the RS232 interface on the switch
Service Service	
Diagnostics	writing to ACA, reading from ACA, writing/reading not OK;
· ·	(display using LEDs on the switch)
Configuration	via the RS232 interface of the switch and via SNMP/Web
Ambient conditions	
Operating temperature	-40 °C 70 °C
Storage/transport temperature	-40 °C 85 °C
Relative humidity (non-condensing)	10 % 95 %
MTBF	370.9 years (MIL-HDBK-217F)
Mechanical construction	
Dimensions (W x H x D)	90 mm x 27 mm x 12 mm
Mounting	plug-in module
Weight	35 g
Protection class	IP40
Cable length	31.5 cm
Mechanical stability	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 g, 10 Hz - 150 Hz, 30 cycles
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m
EMC emitted immunity	EN CEOOD
EN 55022	EN 55022
Approvals Hazardous locations	ISA 12.12.01 Class 1 Div. 2
Shipbuilding	Germanischer Lloyd
Safety of information technology equipment	·
Safety of information technology equipment Safety of industrial control equipment	cUL 60950-1 (pending)  cUL 508
Scope of delivery and accessories	UOL JUU
Scope of delivery	device, operating manual
	correct operating mandai



The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.

