

# ADAM-3011

# ADAM-3013

# ADAM-3014



ADAM-3011

CE FCC FM APPROVED



ADAM-3013

CE FCC FM APPROVED



ADAM-3014

CE FCC FM APPROVED

## Specifications

### Thermocouple Input

- Common Mode Rejection 115 dB min
- Input Type
  

T/C Type	Temperature Range (°C)	Accuracy at 25 °C
J	-40 ~ 760	±2
K	0 ~ 1,000	±2
T	-100 ~ 400	±2
E	0 ~ 1,000	±2
S	500 ~ 1,750	±4
R	500 ~ 1,750	±4
B	500 ~ 1,800	±4

  

  - Isolation 1,000 V<sub>DC</sub> (three way)
  - Output Impedance 0.5 Ω
  - Stability (Temperature Drift) ±2 °C
  - Voltage Output 0 ~ 10 V

### General

- Connectors Screw terminal
- Enclosure ABS
- Indicators Power LED indicator
- Isolation 1,000 V<sub>DC</sub>
- Power Consumption 1.4 W
- Power Input 24 V<sub>DC</sub> ±10%
- Dimensions (W x H x D) 23.2 x 101 x 93.5 mm (0.91" x 3.97" x 3.68")
- Operating Temperature 0 ~ 50 °C (32 ~ 122 °F)
- Storage Temperature -25 ~ 85 °C (-13 ~ 185 °F)

## Ordering Information

- ADAM-3011-AE Isolated thermocouple input module

## Specifications

### RTD Input

- Accuracy ± 0.1% of full range (voltage) or ± 0.15 °C (voltage)  
± 0.2% of full range (current)
- Bandwidth 4 Hz
- Input CMR at DC 92 dB min.
- Input Connections 2/3/4 wires
- Input Type

RTD Type	$\alpha$	Temperature Range (°C)
Pt	0.00385	-100 ~ 100
Pt	0.00385	0 ~ 100
Pt	0.00385	0 ~ 200
Pt	0.00385	0 ~ 600
Pt	0.00385	-100 ~ 0
Pt	0.00385	-100 ~ 200
Pt	0.00385	-50 ~ 50
Pt	0.00385	-50 ~ 150
Pt	0.00392	-100 ~ 100
Pt	0.00392	0 ~ 100
Pt	0.00392	0 ~ 200
Pt	0.00392	0 ~ 600
Ni	N/A	0 ~ 100
Ni	N/A	-80 ~ 100

- Output Range 0 ~ 5 V, 0 ~ 10 V, 0 ~ 20 mA
- Output Resistance < 5 Ω
- Temperature Drift ± 30 ppm of full range

### General

- Connectors Screw terminal
- Enclosure ABS
- Indicators Power LED indicator
- Isolation 1,000 V<sub>DC</sub>
- Power Consumption < 0.95 W
- Power Input 24 V<sub>DC</sub> ±10%
- Dimensions (W x H x D) 23.2 x 101 x 93.5 mm (0.91" x 3.97" x 3.68")
- Operating Temperature 0 ~ 70 °C (32 ~ 158 °F)
- Storage Temperature -25 ~ 85 °C (-13 ~ 185 °F)

## Ordering Information

- ADAM-3013-AE Isolated RTD input module

## Isolated Thermocouple Input Module

## Isolated RTD Input Module

## Isolated DC Input/Output Module

## Specifications

### I/O

- Accuracy ± 0.1% of full range (typical)
- Common Mode Rejection > 100 dB @ 50 Hz/60 Hz
- Current Input Bipolar: ±20 mA  
Unipolar: 0 ~ 20 mA  
Input impedance: 250 Ω
- Current Output 0 ~ 20 mA
- Stability (Temperature Drift) 150 ppm (typical)
- Voltage Input Bipolar input:  
±10 mV, ±50 mV,  
±100 mV, ±0.5 V, ±1.0 V, ±5 V, ±10 V  
Unipolar input:  
0 ~ 10 mV, 0 ~ 50 mV,  
0 ~ 100 mV, 0 ~ 0.5 V,  
0 ~ 1 V, 0 ~ 5 V, 0 ~ 10 V  
Input impedance: 2 MΩ  
Input bandwidth: 2.4 kHz (typical)
- Voltage Output Bipolar: ±5 V, ±10 V  
Unipolar: 0 ~ 10 V  
Impedance: < 50 Ω  
Drive: 10 mA max.

### General

- Connectors Screw terminal
- Enclosure ABS
- Indicators Power LED indicator
- Isolation 1,000 V<sub>DC</sub> (three way)
- Power Consumption 0.85 W (voltage output)  
1.2 W (current output)
- Power Input 24 V<sub>DC</sub> ±10%
- Dimensions (W x H x D) 23.2 x 101 x 93.5 mm (0.91" x 3.97" x 3.68")
- Operating Temperature -10 ~ 70 °C (14 ~ 158 °F)
- Storage Temperature -25 ~ 85 °C (-13 ~ 185 °F)

## Ordering Information

- ADAM-3014-AE Isolated DC input/output module