



**I-8060W**

## I-8060W

### 6-channel Relay Output Module

### Specifications

<b>Digital Output</b>	
Output Channels	6
Output Type	Power Relay, Form C
Relay Contact Voltage Range	0.5A @125VAC ; 0.25A @250VAC 2A@30VDC
Max. load Current	2.0 A at 23°C
Max. Operate Time	10 ms Max.
Max. Release Time	5 ms Max.
Dielectric Strength	Between Open Contacts : 1000Vrms (at 1 Minute) Between Coil and Contacts : 1500Vrms (at 1 Minute)
Relay Life	Mechanical : 100,000,000 min. Electrical : 500, 000 Min. at 30VDC@2A, Resistive
<b>LED Display</b>	
1 LED as Power Indicator	
6 LEDs as Relay output Indicators	
<b>Power</b>	
Power Consumption	0.2A @ 5V = 1W, +/- 5% For Hardware
<b>Environment</b>	
Operating Temperature	-25 to 75 °C
Storage Temperature	-30 to 85 °C
Humidity	5 to 95%, Non-condensing
<b>Dimensions</b>	
30 x 88 x 115 (W x D x H)	

### Ordering information

<b>I-8060W-G CR</b>	6-channel Relay Output Module (Gray Cover) (RoHS)
---------------------	---