


# MNR-330P

## 16-Channel Transportation Standalone NVR with 4-port PoE Connectors with Additional Computing Power



- Maximum Number of Video Devices: 16
- Free License: 16 (16 channels for ACTi and 1 channel for third-party video device)
- Built-in PoE Connectors (4 ports)
- Additional Computing Power
- Video export formats: RAW, AVI, EXE
- Event trigger, response and notification
- Workstation, Web Client, Mobile Client
- Location-based management with e-Map
- Non-ACTi camera support via licensed Camera Device Pack

### ► Solution Diagram



### ► Specifications

#### Device

Product Type	Standalone NVR
Maximum Resolution	Support all ACTi cameras in all resolutions
Maximum Number of Video Devices	16

Maximum Number of POS devices	16 (requires additional license)
Maximum Number of Access Control and Network I/O devices	16 (requires additional license)
Maximum Number of Clients	Local: 1, Remote: 3
Additional Computing Power	Yes

**Hardware**

CPU	Intel Core i5-4300U
RAM	8GB

**License**

Free License	16 (16 channels for ACTi and 1 channel for third-party video device)
--------------	--

**Live View**

Display Layout Mode	Local:1, 3, 4, 5, 6, 8, 9, 10, 12, 16, Remote:1, 3, 4, 5, 6, 8, 9, 10, 12, 16, 18, 24, 25, 35, 36, 48, 49, 64, Custom
Fisheye Dewarping	Yes
Local Live View performance	Please check "Standalone NVR Performance Validator" ( <a href="http://www.acti.com/SANVRPerformance">http://www.acti.com/SANVRPerformance</a> )
Digital Zoom	Yes
Event Status	Display event status upon alarm or upon connection loss or recovery between server and client or when the allocated disk space is full
Instant Playback	Instant Playback in live view window
Embedded websites in Live View	Display and connect to pre-configured embedded website

**Map**

e-Map	Yes
Setup	e-Map image upload, Google maps settings and preset management, camera positioning, vision angle and pointed direction of camera, view positioning, source positioning, extended devices for Point-of-sale (POS), Access Control, Network I/O, Car Park

**PTZ**

PTZ Control	PTZ Control, Speed Control, 32 preset points
-------------	--

**Video**

Compression	H.265, H.264, MPEG-4, MJPEG
-------------	-----------------------------

**Audio**

Audio Type	2-way, Mic-in, Line-in, Line-out
------------	----------------------------------

**Network**

Network Protocol & Service	IPv4/v6, TCP, UDP, DHCP Client, HTTP, DNS, NTP, RTP, RTSP, SMTP, FTP, ICMP, ARP, UPnP, LDAP (client)
Ethernet Port	Total ports: 6 port(s) (WAN) Non-PoE: 2 port(s), Ethernet (1000 Base-T), RJ-45 connector (LAN) PoE: 4 port(s), Ethernet (10/100 Base-T), RJ-45 connector

**Recording**

Scheduled Recording	Yes
---------------------	-----

Event Recording	Yes
Manual Recording	Yes
Event Speed-up Recording	Yes
Dual Stream Management	Yes
Maximum Recording Throughput	192 Mbps

### Search & Playback

Playback Control	Continuous forward and backward playback with speeds 1x/2x/4x/8x/16x or frame-by-frame, pause, stop
Synchronized Playback	4 channels (Local), 16 channels (Remote)
Recording Search	Search video recordings by time, events, channels, bookmarks, notifications and listed as clickable time-based thumbnails for full-size view and snapshot download
Smart Search	Smart search of recorded video by Motion Detection and Tamper
Video Export	RAW, AVI, EXE

### Event

Event Trigger	[NVR]: Disk full, Disk not found, Disk is available, Schedule service start and stop, Video Push start and stop, CPU limit exceeded, [Video Device]: Video motion detection, Passive IR sensor, External device through digital input, Sound detection, Intelligent event detection, Video Push start and stop, Video loss, Video Recovery, Network loss and recovery, [Extended Device]: Point-of-sale (POS) status, Network I/O status, Access Control status, Car park status
Event Response	Pop-up window with live video and event confirmation activation, Switch to hotspot window, Switch to customize view, Command a PTZ device to go to a preset point, Play alert sound, Activate external device through digital output, Execute system command to activate other programs, Upload video or snapshot to FTP server, E-mail notification with snapshots, Push notification

### Redundancy Server

Redundancy Service	Yes, N+1 (With limited functions when NVR 3 server acts as Redundancy server)
--------------------	---

### System

Permission control	Unlimited number of users, Active Directory, Customizable permissions for user groups, Account lockout, Automatic logout after idle, Playback password protected, Password validity period
Client PC Operating System	Windows 7 SP1, Windows 8.1, Windows 10, Windows Server 2008 R2 SP1, Windows Server 2012 R2, Windows Server 2016
Server Operating System	Windows 7 Embedded
Mobile Client Program	Mobile device application (ACTi Mobile Client) supports Live View, PTZ Control, Video Push, Event/time based search and playback, Supported device(s) iPhone, Android device

### Integration

Unified Solution	Fully compatible with ACTi cameras, encoders, central management system, TV wall and intelligent video surveillance software
GPS Position	Manual setting
ONVIF Compliant	Yes, Profile S
Web Browser	IE 11 (Please verify that your computer meets the minimum system requirements for Internet Explorer from Microsoft website.)
Third-party Integration	Point of Sale (POS), Access Control, Network I/O, Parking Management Station (PMS), (Various optional integrations requiring additional license)

**Storage**

System Drive	mSATA SSD, 64GB
Storage Bay	SATA, Max. 1 Disk(s) (without storage disks)
HDD Size	2.5"
Maximum Recording Capacity	1TB x1
Supported Storage	Video Recording: SATA disk, iSCSI Export: iSCSI, USB



**Interface**

Wireless	Built-in GPS, mini-PCIe slot x 4 for optional Wireless modules such as Wi-Fi (IEEE 802.11b/g/n), 4G
External Storage Interface	USB
Local Access	USB joystick, keyboard & mouse
Local Display Interface	HDMI x 1, VGA x 1,

**General**


PoE Output	Maximum 15.4 Watts per port
PoE Power Budget	Maximum 30 W
Power Source	DC 12V, DC 9-36V
Dimensions	(W x H x D): 264.5mm x 75.1mm x 133mm (10.41" x 2.95" x 5.23")
Bundled Accessories	GPS Active Antenna with 5M Cable and SMA Connector
Operating Temperature	0°C ~ 45°C (32°F ~ 113°F)
Remote Access	Workstation, Web Client, Mobile Client
Approvals	CE, FCC, UL, CCC, BSMI, E-Mark
Warranty	2 Year(s)

## ► Photo Indication



- 1 USB 2.0 Ports
- 2 USB 3.0 Port
- 3 HDMI Port
- 4 VGA Connector
- 5 LAN 1 Port
- 6 LAN 2 Port
- 7 Power Status LED
- 8 Power Switch
- 9 HDD Trays
- 10 Reset Button
- 11 HDD Activity LED
- 12 Serial Port
- 13 Power Connector
- 14 Audio Mic-in
- 15 Audio Line-in
- 16 Audio Line-out
- 17 PoE Ports
- 18 Digital Input/Output

## ► Dimension Diagram



Unit: mm [inch]

## ▶ Related Products

### Network & Storage Peripherals - Hard Disk

PHDD-1200



WD WD10JUCT 1TB 2.5" Hard Disk Drive for Data Storage (for MNR-310, MNR-320P, MNR-330P)

### Network & Storage Peripherals - Extended Storage Device

PSTR-0400



PROWARE EN-2126JS6T-SQX 2U 12-Bay NAS RAID Storage Device (for GNR-3000, MNR-320P, MNR-330P, and all GNR and INR Series)

### Network & Storage Peripherals - Wireless Module

PWLM-0104



Advantech EWM-C117FL01E 4G LTE / 3G / 2G Wireless Module for all MNR (except MNR-310), IVS-010, ECD-200 (US)

PWLM-0105



Advantech EWM-C117FL02E 4G LTE / 3G / 2G Wireless Module for all MNR (except MNR-310), IVS-010, ECD-200 (Europe and Asia)

PWLM-0202



Advantech EWM-W161H01E Wi-Fi Module for all MNR (except MNR-310), IVS-010, ECD-200

### Network & Storage Peripherals - Network IO Module

PIOB-0100



Advantech ADAM-6060 6 Digital Input and 6 Digital Output Network I/O Module

### Controllers - Joystick

PJSK-0100



Apem 100-550-BLK-RF Joystick for PTZ Control (for all ENR, INR, and MNR Series)