

Power Adapters

AC power adapters



Features and Benefits

- 100 to 240 VAC power input
- -40 to 75°C operating temperature range (-T models)

Certifications



Introduction

The power adapters in Moxa's Power Adapter Series provide a reliable power source for many Moxa products.

Specifications

Input Power Parameters

Voltage Range	100 to 240 VAC (50 to 60 Hz)
---------------	------------------------------

Power Parameters

Input Plug Type	PWR-AU Models: Australia plug type PWR-CN Models: China plug type PWR-EU Models: Europe plug type PWR-UK Models: United Kingdom plug type PWR-USJP Models: United States/Japan plug type PWR-KR Models: Korea plug type PWR-24250-DT-S1: Desktop
Output Power Rating	PWR-12050 Models: 0.5 A @ 12 VDC PWR-12150 Models: 1.5 A @ 12 VDC PWR-12300 Models: 3 A @ 12 VDC PWR-24250-DT-S1: 2.5 A @ 24 VDC
Output Plug Type	PWR-12050-S1 Models: S-Type 5.5/2.1/7.5 PWR-12050-S2 Models: S-Type 5.5/2.1/9.5 PWR-12150-S2 Models: S-Type 5.5/2.1/9.5 PWR-12300 Models: S-Type 5.5/2.1/7.5 PWR-12150-SA-T Models: L-Type 5.5/2.1/7.5 PWR-24250-DT-S1: S-Type 5.5/2.1/9.5 Outer Diameter: 5.5 ± 0.1 mm (0.22 ± 0.004 in) Inner Diameter: 2.1 ± 0.1 mm (0.08 ± 0.004 in)

Physical Characteristics

<p>Dimensions</p>	<p>PWR-12050-AU-S1: 67.9 x 33.5 x 39.4 mm (2.67 x 1.32 x 1.55 in) PWR-12050-CN-S1: 67.8 x 33.0 x 39.0 mm (2.67 x 1.30 x 1.54 in) PWR-12050-EU-S1: 68.0 x 33.0 x 55.0 mm (2.68 x 1.30 x 2.17 in) PWR-12050-KR-S1: 67.7 x 33.0 x 55.1 mm (2.67 x 1.30 x 2.17 in) PWR-12050-UK-S1: 67.8 x 50.3 x 43.0 mm (2.67 x 1.98 x 1.69 in) PWR-12050-USJP-S1: 67.8 x 33.0 x 39.0 mm (2.67 x 1.30 x 1.54 in) PWR-12050-AU-S2: 67.9 x 39.4 x 42.5 mm (2.67 x 1.55 x 1.67 in) PWR-12050-CN-S2: 67.8 x 33.0 x 39.0 mm (2.67 x 1.30 x 1.54 in) PWR-12050-EU-S2: 68.0 x 33.0 x 55.0 mm (2.68 x 1.30 x 2.17 in) PWR-12050-KR-S2: 67.7 x 33.0 x 55.1 mm (2.67 x 1.30 x 2.17 in) PWR-12050-UK-S2: 67.9 x 50.3 x 43.0 mm (2.67 x 1.98 x 1.69 in) PWR-12050-USJP-S2: 67.8 x 33.0 x 39.0 mm (2.67 x 1.30 x 1.54 in) PWR-12150-WPAU-S2: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in) PWR-12150-WPCN-S2: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in) PWR-12150-WPEU-S2: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in) PWR-12300-WPUK-S2: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in) PWR-12150-WPUSJP-S2: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in) PWR-12150-WPAU-S4: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in) PWR-12150-WPCN-S4: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in) PWR-12150-WPEU-S4: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in) PWR-12150-WPKR-S4: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in) PWR-12150-WPUK-S4: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in) PWR-12150-WPUSJP-S4: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in) PWR-12300-WPAU-S2: 93.0 x 50.0 x 39.6 mm (3.66 x 1.97 x 1.56 in) PWR-12300-WPCN-S2: 93.0 x 50.0 x 39.6 mm (3.66 x 1.97 x 1.56 in) PWR-12300-WPEU-S2: 93.0 x 50.0 x 39.6 mm (3.66 x 1.97 x 1.56 in) PWR-12300-WPUK-S2: 93.0 x 50.0 x 39.6 mm (3.66 x 1.97 x 1.56 in) PWR-12300-WPUSJP-S2: 93.0 x 50.0 x 39.6 mm (3.66 x 1.97 x 1.56 in) PWR-12150-AU-SA-T: 41 x 73.9 x 89.5 mm (1.61 x 2.91 x 3.52 in) PWR-12150-CN-SA-T: 32 x 60 x 88 mm (1.26 x 2.36 x 3.46 in) PWR-12150-EU-SA-T: 32 x 85.3 x 88 mm (1.26 x 3.36 x 3.46 in) PWR-12150-UK-SA-T: 50 x 91 x 82.5 mm (1.97 x 3.58 x 3.25 in) PWR-12150-USJP-SA-T: 32 x 70.3 x 88 mm (1.26 x 2.77 x 3.46 in) PWR-24250-DT-S1: 133 x 59.1 x 34.4 mm (5.24 x 2.33 x 1.35 in)</p>
<p>Weight</p>	<p>PWR-12050 Models: 71~87 g (0.16 ~ 0.19 lb) PWR-12150 Models: 200 g (0.44 lb) PWR-12150-S2 Models: 115 g (0.25 lb) PWR-12300-S1 Models: 163 g (0.36 lb) PWR-24250-DT-S1: 330 g (0.73 lb)</p>
<p>Cord Length</p>	<p>PWR-12050 Models: 1500±100 mm (59.06±3.94 in) PWR-12150 Models: 1500±100 mm (59.06±3.94 in) PWR-12300 Models: 1500±100 mm (59.06±3.94 in) PWR-24250-DT-S1: 1500±100 mm (59.06±3.94 in)</p>
<p>Environmental Limits</p>	
<p>Operating Temperature</p>	<p>Standard Models: 0 to 40°C (32 to 104°F) Wide Temp. Models: -40 to 75°C (-40 to 167°F)</p>
<p>Storage Temperature</p>	<p>Standard Models: -20 to 70°C (-4 to 158°F) Wide Temp. Models: -40 to 75°C (-40 to 167°F)</p>
<p>Standards and Certifications</p>	
<p>Safety</p>	<p>PWR-12050-AU Models: RCM PWR-12050-CN Models: CCC PWR-12050-EU Models: CE/GS PWR-12050-KR Models: KCC PWR-12050-UK Models: CE PWR-12050-USJP Models: FCC/UL/PSE PWR-12150 Models: CE/FCC/UL/RCM/PSE/CCC/GS/KCC PWR-12300 Models: CE/FCC/UL/RCM/PSE/CCC/GS PWR-12150-AU-SA-T: RCM PWR-12150-CN-SA-T: CCC PWR-12150-EU-SA-T: TUV/CE/GS PWR-12150-UK-SA-T: CE PWR-12150-USJP-SA-T: FCC/UL/PSE PWR-24250-DT-S1: CE/FCC/UL/RCM/PSE/CCC/GS</p>

Warranty

Warranty Period	1.5 years
Details	See www.moxa.com/warranty

Ordering Information

Model Name	Barrel-plug Type	Input-plug Type	Output Rating	Operating Temperature
PWR-12050-AU-S1	Locking	AU	0.5 A @ 12 VDC	0 to 40°C
PWR-12050-CN-S1	Locking	CN	0.5 A @ 12 VDC	0 to 40°C
PWR-12050-EU-S1	Locking	EU	0.5 A @ 12 VDC	0 to 40°C
PWR-12050-KR-S1	Locking	KR	0.5 A @ 12 VDC	0 to 40°C
PWR-12050-UK-S1	Locking	UK	0.5 A @ 12 VDC	0 to 40°C
PWR-12050-USJP-S1	Locking	US/JP	0.5 A @ 12 VDC	0 to 40°C
PWR-12050-AU-S2	Non-locking	AU	0.5 A @ 12 VDC	0 to 40°C
PWR-12050-CN-S2	Non-locking	CN	0.5 A @ 12 VDC	0 to 40°C
PWR-12050-EU-S2	Non-locking	EU	0.5 A @ 12 VDC	0 to 40°C
PWR-12050-KR-S2	Non-locking	KR	0.5 A @ 12 VDC	0 to 40°C
PWR-12050-UK-S2	Non-locking	UK	0.5 A @ 12 VDC	0 to 40°C
PWR-12050-USJP-S2	Non-locking	US/JP	0.5 A @ 12 VDC	0 to 40°C
PWR-12150-WPAU-S2	Non-locking	AU	1.5 A @ 12 VDC	0 to 40°C
PWR-12150-WPCN-S2	Non-locking	CN	1.5 A @ 12 VDC	0 to 40°C
PWR-12150-WPEU-S2	Non-locking	EU	1.5 A @ 12 VDC	0 to 40°C
PWR-12150-WPUK-S2	Non-locking	UK	1.5 A @ 12 VDC	0 to 40°C
PWR-12150-WPUSJP-S2	Non-locking	US/JP	1.5 A @ 12 VDC	0 to 40°C
PWR-12150-WPAU-S4	Locking	AU	1.5 A @ 12 VDC	0 to 40°C
PWR-12150-WPCN-S4	Locking	CN	1.5 A @ 12 VDC	0 to 40°C
PWR-12150-WPEU-S4	Locking	EU	1.5 A @ 12 VDC	0 to 40°C
PWR-12150-WPKR-S4	Locking	KR	1.5 A @ 12 VDC	0 to 40°C
PWR-12150-WPUK-S4	Locking	UK	1.5 A @ 12 VDC	0 to 40°C
PWR-12150-WPUSJP-S4	Locking	US/JP	1.5 A @ 12 VDC	0 to 40°C
PWR-12300-WPAU-S2	Locking	AU	3 A @ 12 VDC	0 to 40°C
PWR-12300-WPCN-S2	Locking	CN	3 A @ 12 VDC	0 to 40°C
PWR-12300-WPEU-S2	Locking	EU	3 A @ 12 VDC	0 to 40°C
PWR-12300-WPUK-S2	Locking	UK	3 A @ 12 VDC	0 to 40°C
PWR-12300-WPUSJP-S2	Locking	US/JP	3 A @ 12 VDC	0 to 40°C
PWR-12150-AU-SA-T	Locking	AU	1.5 A @ 12 VDC	-40 to 75°C
PWR-12150-CN-SA-T	Locking	CN	1.5 A @ 12 VDC	-40 to 75°C
PWR-12150-EU-SA-T	Locking	EU	1.5 A @ 12 VDC	-40 to 75°C
PWR-12150-UK-SA-T	Locking	UK	1.5 A @ 12 VDC	-40 to 75°C
PWR-12150-USJP-SA-T	Locking	US/JP	1.5 A @ 12 VDC	-40 to 75°C
PWR-24250-DT-S1	Non-locking	Desktop	2.5 A @ 24 VDC	0 to 40°C

© Moxa Inc. All rights reserved. Updated Sep 15, 2022.

This document and any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of Moxa Inc. Product specifications subject to change without notice. Visit our website for the most up-to-date product information.