



### Outdoor Remote Power Systems

#### Features

- Complete 200W Remote Power Solution for Off-Grid Operation
- Weatherproof Outdoor Enclosures with up to 400Ah Battery
- Enclosures can be Wall or Pole Mounted (pole not included)
- High Performance Sealed Lead Acid AGM Batteries
- MPPT and PWM Solar Charge Controllers, some with PoE output
- Thermostatically Controlled Ventilation



RPL 200W  
Solar System

#### Applications

- Wireless Base Stations
- Remote Lighting
- Surveillance Cameras
- Wireless Bridge and Repeaters
- Off-Grid Power
- Backup Power

#### Description

The RemotePro® 200W Series outdoor power systems are designed for applications that require a primary off-grid power source to run various equipment. The vented weatherproof enclosures have generous space available inside for mounting customer equipment. Multiple mounting brackets are welded inside the enclosure for mounting DIN rails or flat plates.

The systems are available with MPPT or PWM temperature compensated solar charge controllers. Some of the PWM systems are available with 24V or 48V 10/100 Passive PoE outputs. The solar controllers turn off the load automatically if the battery voltage drops too low, in order to preserve battery life. The load turns on automatically once the battery voltage recovers.




The outdoor enclosures are powder coated steel or aluminum. They are hinged and gasket sealed with a locking closure that accepts a common padlock for security. They have four cable gland ports for CAT5/6 cable, antenna cables/connectors or other cabling. Included is a thermostatically controlled fan assembly which turns on automatically when the temperature exceeds 45°C.

The high quality solar panels have a 25 year power output guarantee and a +5W output tolerance. The enclosures and solar mount can be mounted to a wall or pole (2-4") with the included mounting system.

Batteries are a Non-Spillable Valve Regulated Sealed Lead Acid Absorbed Glass Matt (AGM) type which have excellent temperature and deep discharge performance. Expected battery life exceeds 5 years.

The systems come with all cabling required to connect the batteries to the controller and 20' outdoor rated cable to connect the solar panels to the controller.

## Specifications – Controller Specific

	<i>PWM-PoE PWM-PoE+</i>	<i>PWM</i>	<i>MPPT</i>
<b>Controller Type</b>	10A PWM with PoE	PWM with LCD Display	MPPT with display and RS485
<b>Controller Outputs</b>	24V 1.5A/10A wire terminal and 24V or 48V Passive PoE/PoE+	20A Wire Terminal	20A Wire Terminal
<b>Bulk Charge</b>	28.6V @ 24V Battery	14.4V @ 12V Battery 28.8V @ 24V Battery	14.4V @ 12V Battery 28.8V @ 24V Battery
<b>Float Charge</b>	27.3V @ 24V Battery	13.8V @ 12V Battery 27.6V @ 24V Battery	13.8V @ 12V Battery 27.6V @ 24V Battery
<b>Over-discharge protection</b>	20V @ 24V Battery	11.1V @ 12V Battery 22.2V @ 24V Battery	11.1V @ 12V Battery 22.2V @ 24V Battery
<b>Over-discharge recovery volts</b>	24.3V @ 24V Battery	12.6V @ 12V Battery 25.2V @ 24V Battery	12.6V @ 12V Battery 25.2V @ 24V Battery
<b>Controller Self Consumption</b>	<0.5W	<0.3W	<1W
			

## Specifications – Enclosure Specific

	<i>RPS</i>	<i>RPL</i>	<i>RPSTL</i>
<b>Battery Type</b>	Maintenance Free Non-Spillable Valve Regulated Sealed Lead Acid AGM		
<b>Battery Life</b>	5+ years		
<b>Enclosure Type</b>	ENC-AL-12x14x15 Pole/Wall Mount, Powder Coat Aluminum	ENC-AL-21x14x15 Pole/Wall Mount, Powder Coat Aluminum	ENC-STL-24x24x16 Pole/Wall Mount, Powder Coat Steel
<b>Enclosure Size</b>	12 x 14 x 15" (305 x 356 x 381mm)	21 x 14 x 15 (537 x 356 x 381mm)	23.9 x 23.9 x 16.1" (608 x 608 x 409.5mm)
<b>Internal Mount Features</b>	DIN Rail/Flat Plate Mounting Brackets Welded to Door and Back		
<b>Solar Panel Dims (L x W x T)</b>	200W Solar Array 24.4" x 61" x 1.2" (620 x 1540 x 30mm)		
<b>Operating Temperature</b>	-30°C to +60°C (-22°F to 140°F)		
<b>System Weight (no batteries)</b>	41 lb (19 kg)	48 lb (22 kg)	109 lb (49 kg)
<b>Battery Weight</b>	40.3 lb (18.3 kg) (Each 50Ah Battery)		
<b>Wind Speed Rating</b>	90MPH		
<b>Warranty</b>	3 Years		



*RPS Enclosure interior  
without batteries or controller*



*RPL Enclosure interior  
without batteries or controller*



*RPSTL Enclosure interior  
without batteries or controller*

## System Ordering:

Model #	Enclosure Type	Battery Voltage	Battery Capacity @12V	Rated Continuous Power with 6hrs Peak Sun	Backup Time @ Rated Power	Controller Type	Outputs	Solar Panel Size
RPS2424-100-200	Small Aluminum	24V	100Ah	25W	>24hrs	PWM-PoE	24V 1.5A + 24V 30W Pasv PoE	200W
RPS2448-100-200	Small Aluminum	24V	100Ah	25W	>24hrs	PWM-PoE	24V 1.5A +48V 30W Pasv PoE	200W
RPS24AT-100-200	Small Aluminum	24V	100Ah	25W	>24hrs	PWM-PoE+	24V 10A +48V 30W PoE+	200W
RPS12/24-100-200	Small Aluminum	12/24V	100Ah	25W	>24hrs	PWM	12/24V 20A	200W
RPS12/24M-100-200	Small Aluminum	12/24V	100Ah	25W	>24hrs	MPPT	12/24V 20A	200W
RPL2424-200-200	Large Aluminum	24V	200Ah	43W	>32hrs	PWM-PoE	24V 1.5A + 24V 30W Pasv PoE	200W
RPL2448-200-200	Large Aluminum	24V	200Ah	43W	>32hrs	PWM-PoE	24V 1.5A +48V 30W Pasv PoE	200W
RPL24AT-200-200	Large Aluminum	24V	200Ah	43W	>32hrs	PWM-PoE+	24V 10A +48V 30W PoE+	200W
RPL12/24-200-200	Large Aluminum	12/24V	200Ah	43W	>32hrs	PWM	12/24V 20A	200W
RPL12/24M-200-200	Large Aluminum	12/24V	200Ah	43W	>32hrs	MPPT	12/24V 20A	200W
RPSTL12/24M-200-200	Large Steel	12/24V	200Ah	43W	>32hrs	MPPT	12/24V 20A	200W

## Part Number Definition:

### RPL 12/24M-200-200

<u>Enclosure Type</u> S - Small Aluminum L - Large Aluminum STL - Large Steel	<u>Battery Voltage/PoE</u> 2424 - 24VDC, 24V PoE 2448 - 24VDC, 48V PoE 24AT - 24VDC, PoE+ 12/24 - 12/24V PWM 12/24M - 12/24V MPPT 12/48M - 12/24/48V MPPT	<u>12V Storage Capacity</u> 100 - 100Ah 200 - 200Ah 400 - 400Ah	<u>Solar Panel Output</u> 100 - 100 Watt 200 - 200 Watt 400 - 400 Watt
--	---	--	---



AGM 12V 52Ah Battery

For further information contact:

[Tyconsystems.com](http://Tyconsystems.com)



930 W 14600 S Ste 600  
Bluffdale, UT 84065  
PH: 801-432-0003  
FAX: 801-618-4220