



RemotePro® TPDIN-SC48-20 Series

DATA SHEET

Outdoor Remote Power Systems

Features

- Complete Remote Power Solutions for Off-Grid Operation.
- TPDIN-SC48-20 Remote Manageable MPPT Solar Controller with Gigabit PoE Switch
- Supports up to 157W continuous power with 6hrs peak sun.
- Weatherproof Outdoor Enclosures with up to 720Ah Battery
- Solar Mounts: Pole/Wall and Ground Mounts
- High Performance Sealed Lead Acid AGM Batteries
- Thermostatically Controlled Ventilation



RPAL 720W
Solar System

Applications

- Wireless Base Stations
- Remote Lighting
- Surveillance Cameras
- Wireless Bridge and Repeaters
- Off-Grid Power
- Remote Cabins

Description

The RemotePro® TPDIN-SC48-20 Series outdoor power systems are designed for applications that require a primary off-grid power source with an integrated 24/48V PoE Gigabit Switch to power up to 7 PoE devices. The vented weatherproof enclosures have generous space available inside for mounting customer equipment. Multiple mounting brackets are welded inside the enclosure for mounting DIN rails or flat plates.

The systems have a unique MPPT temperature compensated solar charge controller that provides 7 Gigabit PoE switch ports that are capable of 24V or 48V passive PoE or 802.3at PoE. The controller is remotely manageable over the network. It has user programmable controls to control each port based on parametric limits and provides programmable email alerts. The switch is VLAN compatible. The solar controllers turn off the load automatically if the battery voltage drops too low, to preserve battery life. The load turns on automatically once the battery voltage recovers.

The outdoor enclosures are powder coated steel pole/wall mount or diamond plate aluminum ground mounted type. They are hinged and gasket sealed with locking closures. They have four cable gland ports for CAT5/6 cable, antenna cables/connectors or other cabling. Included is a thermostatically controlled fan assembly which turns on automatically when the temperature exceeds 45°C.

The high-quality solar panels have a 25-year power output guarantee and a +5W output tolerance.

Batteries are maintenance free, Non-Spillable, Valve Regulated, Sealed Lead Acid Advance Glass Matt (AGM) type which have excellent temperature and deep discharge performance. Expected battery life exceeds 5 years.

The systems come with all cabling required to connect the batteries to the controller and 20' outdoor rated cable to connect the solar panels to the controller. The ground mount systems include concrete anchors for securing the solar mount.

Specifications

	RPSTL	RPAL
Battery Type	Maintenance Free, Non-Spillable, Valve Regulated Sealed Lead Acid, AGM	Maintenance Free, Non-Spillable, Valve Regulated, Sealed, Pure Lead Carbon AGM
Battery Life	5+ years	
Battery Voltage	48VDC	
Controller Type	TPDIN-SC48-20 48V MPPT Solar Controller with Remotely Manageable Gigabit PoE Switch	
Controller Outputs	Qty 4 Gigabit 802.3at Ports (also configurable as 24V/48V 0.645A Passive PoE) Qty 3 24V/48V 0.645A Gigabit Passive PoE Ports PoE Power is supplied on pins 4,5(V+) and 7,8(V-) (Mode B) Qty 1 Auxiliary 24V/48V 2.25A wire terminal output	
Bulk Charge	57.6V	
Float Charge	55.2V	
Over-discharge protection	42V- 48V (settable in user interface)	
Over-discharge recovery volts	44V– 54V (settable in user interface)	
Controller Self Consumption	3.5W Typical	
Enclosure Type	ENC-STL-24x24x16 Pole/Wall Mount, Powder Coat Steel	ENC-AL-65x18x20 Ground Mount, Diamond Plate Aluminum
Enclosure Size	23.9 x 23.9 x 16.1" (608 x 608 x 409.5mm)	65 x 18 x 20" (1651 x 457 x 508mm)
Internal Mount Features	DIN Rail/Flat Plate Mounting Brackets Welded to Door and Back	
Solar Panel Dims (L x W x T)	400W Solar Array 49" x 61" x 1.2" (1240 x 1540 x 30mm) 720W Solar Array 78 x 77 x 1.6" (1980 x 1956 x 40mm)	
Operating Temperature	-30°C to +60°C (-22°F to 140°F)	
System Weight (no batteries)	136 lb (62 kg) 400W System 377 lb (171 kg) 720W System	394 lb (179 kg) 720W System
Battery Weight	40.3 lb (18.3 kg) (Each 50Ah Battery)	127 lb (57.6 kg) (Each 180Ah Battery)
Wind Speed Rating	90MPH	
Warranty	3 Years	



TPDIN-SC48-20 MPPT
Controller with manageable 7
Port Gigabit PoE Switch



RPSTL Enclosure interior
without batteries or controller



RPAL Diamond Plate Aluminum Ground Mount



AGM 12V 52Ah Battery



AGM 12V 180Ah Battery


RemotePro® TPDIN-SC48-20 Series

System Ordering:

Model #	Enclosure Type	Battery Voltage	Battery Capacity @12V	Rated Continuous Power with 6hrs Peak Sun	Backup Time @ Rated Power	Controller Type	Output	Solar Panel Size
RPSTL48-400-400	Large Steel	48V	400Ah	87W	>31hrs	TPDIN-SC48-20	24/48V POE 24/48V Aux	400W
RPSTL48-400-720	Large Steel	48V	400Ah	100W	>24hrs	TPDIN-SC48-20	24/48V POE 24/48V Aux	720W
RPAL48-720-720	Ground Mount Aluminum	48V	720Ah	157W	>24hrs	TPDIN-SC48-20	24/48V POE 24/48V Aux	720W

Part Number Definition:

RPAL 48-720-720



RPSTL 400W 4 Panel Solar System



RPSTL 720W 2 Panel Solar System

For further information contact:

Tyconsystems.com

