SEAL SHIELD™

SEAL CLEAN™
WATERPROOF KEYBOARD

Model: SSKSV207, SSWKSV207, SSKSV207L, SSWKSV207L

Seal Clean Waterproof Keyboards from Seal Shield™. 100% waterproof & dishwasher-safe keyboard is IP68-certified and designed to withstand industrial-grade disinfectants & cleaners. True type keyboard with tactile feel and full travel keys for smooth and natural typing. Features a Quick Connect or Long Cable with RF shielding and a Seal Cap™ for easy plug-and-play. Full-Size numeric keypad and Laser-etched keycaps enhance durability and product longevity throughout regular and vigorous cleaning.

FEATURES:

100% Waterproof, Dishwasher-Safe, & Fully Submersible

IP68-Certified

Full-Size Numeric Keypad and Laser Etched Keycaps

Gold Coated USB with Seal Cap™ USB Protector

Cable Options Quick Connect or Long Cable with RF Shielding

Designed to Withstand Industrial-Grade Disinfectants & Cleaners

Standard Style Keyboard for Smooth Typing

ABS Plastic with Stainless Steel Screws & Non-Corrosive Components

SSKSV207

SSWKSV207

SSKSV207L

SSWKSV207L

ADVANCED CLEANING CAPABILITIES

· *Dishwasher-Safe*

Compatible with Spray & Wipe Disinfectant Products:

· *Clorox Healthcare®*

· *Lysol®*

· *PDI Products*

· *Bleach, Ethanol, IPA, Quats, Citric Acid, & Hydrogen Peroxide, and Other Industrial-Grade Cleaners and Disinfectants*

CLOROX
HEALTHCARE®
COMPATIBLE

SEAL CLEAN™
WATERPROOF KEYBOARD
Model: SSKSV207, SSWKSV207, SSKSV207L, SSWKSV207L

TECHNICAL DATA:

Compatibility:	Windows©
Construction:	ABS Plastic (Standard Style)
Net Dimensions L x W x H:	18.07 x 6.85 x 1.38 in (45.9 x 17.4 x 3.5 cm)
Key Layout:	104 US Language
Net Weight:	*207:* 1.93 lb (0.875 kg) *207L:* 1.87 lb (0.850 kg)
Gross Weight:	*207:* 2.31 lb (1.050 kg) *207L:* 2.26 lb (1.025 kg)
Cable Length:	SSKSV207L, SSWKSV207L: 6 ft.(1.83m) USB Extension Cable SSKSV207, SSWKSV207: 6in (15cm) Quick Connect Cable with 6 ft.(1.83m) USB Extension Cable
Connection Type:	Gold Plated USB (can support PS/2 technology)
Key Switch Force:	53 ±7 gf
Key Switch Life Cycle:	Greater Than 10 Million Keystrokes
Key Switch Type:	Membrane Key Switch with Tactile Feedback
Keycaps Imaging Type:	Laser Etched
Total Key Travel:	4.0 ± 0.2mm
Operating Current:	60mA
Operating Voltage:	5VDC
Storage Temperature:	-5° - 140° F (-20° to 60° C)
EMI - RFI:	Conforms to FCC Rules for Class B Computing Device
Waterproof/Dustproof Ratings:	IP68, NEMA 4X
Approvals/Certifications:	FCC, CE, RoHS, WEEE, WHQL, ICES-003, EAC, KC, RCM, and cULus, REACH, Cal Prop 65

Limited 2-Year Warranty