

SEAL STORM WASHABLE KEYBOARD

Model: STK503, STWK503, STK503RED, STK503P & STWK503P

Seal Storm Keyboards from Seal Shield. True type keyboard with tactile feel and full travel keys for smooth and natural typing. Features a USB Connection Cable with RF shielding and a Seal Cap $^{\rm TM}$ for easy plug-and-play with PS/2 compatibility. Washable & dishwasher-safe keyboard is IP66- certified and designed to withstand industrial-grade disinfectants & cleaners. Laser-etched keycaps enhance durability and product longevity throughout regular and vigorous cleaning. ABS plastic construction with steel screws.

FEATURES:



IP66-Certified Washable & Dishwasher-Safe,



Gold Coated USB Cable, RF Shielding, & Seal Cap™ USB Protector



ABS Plastic Keyboard with Stainless Steel Screws and Non-Corrosive Components



Full-Size Numeric Keypad and Laser Etched Keycaps



Designed to Withstand Industrial-Grade Disinfectants & Cleaners



Standard Style Keyboard for Smooth Typing



STK503, STK503P





STK503RED

STWK503, STWK503P

ADVANCED CLEANING CAPABILITIES

· Dishwasher-Safe

Compatible with Spray & Wipe Disinfectant Products:

- · Clorox Healthcare®
- · Lysol®
- · PDI Products
- · Bleach, Ethanol, IPA, Quats, Citric Acid, & Hydrogen Peroxide, and Other Industrial-Grade Cleaners and Disinfectants





SEAL STORM WASHABLE KEYBOARD

Model: STK503, STWK503, STK503RED, STK503P & STWK503P

TECHNICAL DATA

| Compatibility: | Windows® |
|-----------------------------|--|
| Key Layout: | 104 US Language |
| Net Dimension: | 17.9in x 7.3in x 1in (45.5cm x 18.6cm x 2.6cm) |
| Net Weight: | 1.37 lbs (0.625 kg) |
| Gross Weight: | 1.71 lbs (0.775 kg) |
| Cable Length: | 6.0 feet (1.8m) with Seal Cap™ |
| Connection Type: | Gold-plated USB, PS/2 Compatibility |
| Key Switch: | Membrane key switch with tactile feedback |
| Key Switch Life Cycle: | Greater than 10 million keystrokes |
| Key Switch Operating Force: | 55 ± 10 gf |
| Keycaps Type: | Laser Etched |
| Total Key Travel: | 0.157 ± .019 in (4 ± 0.5mm) |
| Operating Voltage: | 5VDC |
| Operating Current: | 500mA |
| EMI - RFI: | Conforms to FCC Rules for Class B Computing Device |
| Approvals/Certifications: | IP66, RoHS, WEEE, CE, FCC, ICES-003, WHQL, RCM, REACH, Cal Prop 65 |



Copyright© 2022, Seal Shield, LLC. All rights reserved. All other trademarks and trade names are those of their respective owners

Limited 2-Year Warranty