

SEAL STORM WATERPROOF WIRELESS MOUSE - AES128 ENCRYPTION

Model: STM042WE, STWM042WE

Seal Shield Seal Storm Wireless Mouse has a 100% waterproof & dishwasher-safe rating that is IP68-certified and designed to withstand industrial-grade disinfectants & cleaners. A natural design stands up to frequent and vigorous cleaning. Features a convenient wireless connection & includes a charging base with 3 universal USB ports (charging base is not waterproof). PS/2 compatible.

FEATURES:



IP68-Certified 100% Waterproof, Dishwasher-Safe & Fully Submersible



Designed to Withstand Industrial-Grade Disinfectants & Cleaners



Secure Wireless Encryption & Charging Base with 3 Universal USB Ports



Battery Charge Indicator Light



Two Button Mouse with Scroll Wheel



ABS Plastic with Silicone Scroll Wheel, Stainless Steel Screws & Non-Corrosive Components



STWM042WE (White)





STM042WE

ADVANCED CLEANING CAPABILITIES

· Dishwasher-Safe

Compatible with Spray & Wipe Disinfectant Products:

- · Clorox Healthcare®
- · Lysol®
- · PDI Products
- · Bleach, Ethanol, IPA, Quats, Citric Acid, & Hydrogen Peroxide, and Other Industrial-Grade Cleaners and Disinfectants





SEAL STORM WATERPROOFWIRELESS MOUSE - AES128 ENCRYPTION

Model: STM042WE, STWM042WE

TECHNICAL DATA:

| Compatibility: | Windows® |
|-------------------------------|--|
| Construction: | ABS Plastic |
| Design: | 2 Button with Scroll Wheel (clickable) |
| Net Dimension: | 4.6 x 2.35 x 1.43 in (11.7 x 5.96 x 3.62 cm) |
| Base Dimensions: | 3.9 x 4.1 x 3.9 in (10.0 x 10.4 x 10.0 cm) |
| Net Weight: | 0.17 lb, 0.080 kg(Mouse) 1.10 lb, 0.150 kg(Base) |
| Gross Weight: | 0.66 lb (0.30 kg) |
| Base Cable Length: | 6 ft (1.83 m) |
| Connection Type: | 2.4 GHz RF Wireless (Dongle Reciever USB) PS/2 Compatible |
| Button Switch Force: | 100 ± 20 gf |
| Button Switch Life Cycle: | >10 Million Clicks |
| Scroll Type: | Scroll Wheel |
| Resolution: | 1000 DPI |
| Optical Technology: | LED |
| Operating Voltage: | 3.7VDC |
| Battery mAh: | 130mAh |
| Battery Type: | LiON |
| Storage Temperature: | 5° - 140° F (-15° to 60° C) |
| EMI - RFI: | Conforms to FCC Rules for Class B Device |
| Waterproof/Dustproof Ratings: | IP68, NEMA 4X |
| Approvals/Certifications: | FCC, CE, RoHS, WEEE, REACH, RSS-210, RCM |



Copyright© 2022, Seal Shield, LLC. All rights reserved. All other trademarks and trade names are those of their respective owners Limited 2-Year Warranty