

## SEAL GLOW 2™ WATERPROOF KEYBOARD

Model: S106G2, SW106G2

Seal Glow 2™ Waterproof Keyboards from Seal Shield have a 100% waterproof & dishwasher-safe rating that is IP68-certified and designed to withstand industrial-grade disinfectants & cleaners. LED backlit characters provide non-intrusive visibility assistance & location in darker settings with a full-size numeric keypad for easy entry of numbers. Laser-etched keycaps enhance durability and product longevity throughout regular and vigorous cleaning. Features a Gold-Plated USB Quick Connect™ cable for easy plug-and-play.

### FEATURES:



100% Waterproof,  
Dishwasher-Safe,  
& Fully Submersible



Gold Coated USB  
Quick Connect Cable  
with Seal Cap™ USB  
Protector



Full-Size Numeric  
Keypad and  
Laser Etched Keycaps



LED Backlit Illuminated  
Characters



Designed to Withstand  
Industrial-Grade  
Disinfectants & Cleaners



UV Reinforced Key  
Caps



Fully Sealed Silicone  
Keyboard is IP68-Certified



Compact Footprint



S106G2



SW106G2

### ADVANCED CLEANING CAPABILITIES


- Dishwasher-Safe
- Compatible with Spray & Wipe Disinfectant Products:
  - Clorox Healthcare®
  - Lysol®
  - PDI Products
  - Bleach, Ethanol, IPA, Quats, Citric Acid, & Hydrogen Peroxide, and Other Industrial-Grade Cleaners and Disinfectants



## SEAL GLOW 2™ WATERPROOF KEYBOARD

Model: S106G2, SW106G2

### TECHNICAL DATA:

Compatibility:	Windows® 10, x64
Key Layout:	103 US Language
Net Dimensions:	15.15 x 5.43 x 0.78 in (38.5 x 13.8 x 2 cm)
Net Weight:	1.02 lbs (0.465 kg)
Net Weight:	1.28 lbs (0.585 kg)
Cable Length:	6in( 15cm ) Quick Connect™ with USB Extension Cable
Connection Type:	Gold Plated USB
Key Switch Type:	Carbon point activation with Tactile Feedback
Key Switch Force:	150 ±15 gf
Key Switch Life Cycle:	Greater than 10 Million keystrokes
Keycaps Imaging Type:	Laser Etched
Power Consumption:	70mA Maximum (with LED lights ON)
Total Key Travel:	0.063 ± 0.0196 in (1.6 ± 0.5 mm)
Operating Voltage:	5VDC
Operating Voltage:	100mA
Storage Temperature:	-5° - 140° F (-20° to 60° C)
EMI - RFI:	Conforms to FCC Rules for Class B Device
Waterproof/Dustproof Ratings:	IP68, NEMA 4X
Approvals/Certifications:	RoHS, WEEE, CE, FCC, ICE-003, RCM, REACH, WHQL, Cal Prop 65 



Copyright© 2022, Seal Shield, LLC. All rights reserved. All other trademarks and trade names are those of their respective owners.

Limited 2-Year Warranty