

SEAL GLOW 2 WATERPROOF KEYBOARD

BACKLIT MAGNETIC BACKING


Model: S106G2M, SW106G2M

Seal Glow 2 Waterproof Backlit Keyboards with Magnetic Backing from Seal Shield have a 100% waterproof & dishwasher-safe rating that is IP68-certified and designed to withstand industrial-grade disinfectants & cleaners. Quiet Touch™ LED backlit characters provide non-intrusive visibility assistance & easy location in darker settings with a full-size numeric keypad for easy entry of numbers. Laser-etched keycaps enhance durability and product longevity throughout regular and vigorous cleaning. Features a Gold-Plated USB Quick Connect™ cable for easy plug

FEATURES:



100% Waterproof,
Dishwasher-Safe,
& Fully Submersible



Fully Sealed Silicone
Keyboard is IP68-Certified



Gold Coated USB
Quick Connect Cable
with Seal Cap™ USB
Protector



Full-Size Numeric Keypad,
Magnetic Backing,
& Laser Etched Keycaps



Designed to Withstand
Industrial-Grade
Disinfectants & Cleaners



LED Backlit
Illuminated Characters
with Magnetic Backing



UV Reinforced Key
Caps



Compact Footprint



S106G2M



SW106G2M

ADVANCED CLEANING CAPABILITIES

- Dishwasher-Safe
- Compatible with Spray & Wipe Disinfectant Products:
 - Clorox Healthcare®
 - Lysol®
 - PDI Products
 - Bleach, Ethanol, IPA, Quats, Citric Acid, & Hydrogen Peroxide, and Other Industrial-Grade Cleaners and Disinfectants



SEAL GLOW 2 WATERPROOF KEYBOARD

BACKLIT MAGNETIC BACKING

Model: S106G2M, SW106G2M

TECHNICAL DATA:

Compatibility:	Windows® 10, x64
Key Layout:	103 US Language
Net Dimensions:	15.15 x 5.43 x 0.78 in (38.5 x 13.8 x 2 cm)
Net Weight:	0.99 lbs (0.450 kg)
Gross Weight:	1.34 lbs (0.610 kg)
Cable Length:	6in(15cm) Quick Connect™ with USB Extension Cable
Connection Type:	Gold Plated USB
Key Switch Type:	Carbon point activation with Tactile Feedback
Key Switch Force:	150 ± 15 gf
Key Switch Life Cycle:	Greater than 10 Million keystrokes
Keycaps Imaging Type:	Laser Etched
Operating Current:	100mA
Operating Voltage:	+ 5VDC ± 5%
Total Key Travel:	0.063 ± 0.0196 in (1.6 ± 0.5 mm)
Storage Temperature:	-5° - 140° F (-20° to 60° C)
EMI - RFI:	Conforms to FCC Rules for Class B Device
Waterproof/Dustproof Ratings:	IP68, NEMA 4X
Approvals/Certifications:	RoHS, WEEE, CE, FCC, ICES-003, RCM, REACH, Cal Prop 65



Copyright© 2022, Seal Shield, LLC. All rights reserved. All other trademarks and trade names are those of their respective owners.

Limited 2-Year Warranty