

High Power Dual Output PoE Injectors

Features

- Input Voltage 12VDC, 24VDC or 110VAC
- Dual 802.3af/at outputs
- High Power Output to 70W
- Surge Protected to 15kV
- Dual DC Inputs for Connecting 2 Power Sources
- 10/100 Data Compatibility, Shielded Connectors
- Short Circuit, Over Current and Reverse/Over Voltage Protection
- Industrial Temperature Range, DIN Rail Mountable



TP-POE-48Dx2

Applications

- 12VDC or 24VDC Remote Power Systems running on batteries
- 110/220VAC Backup Power Systems
- Power a Camera and Wireless using a single PoE Injector
- Power a Wireless AP and Backhaul using a single PoE injector

Description

The TP-DCDC-xx48DX2-HP and TP-POE-HP-48DX2 are unique high power PoE injectors with Dual 802.3af/at compatible outputs. This means that two devices can be powered from a single PoE injector. The data path between the units is handled by the injector so no PoE switch is required.

There are models that will run on 12VDC or 24VDC as well as 110/220VAC grid power. The different models have different total outputs up to 70W.

They have two inputs for connecting 2 power sources, like a primary and backup power source. They have various protections for short circuit, overload and surges caused by ESD or lightning. The built-in surge protection protects sensitive connected devices from damage due to surges on data and PoE lines. All 8 wires are protected.

The input voltage and output voltage are isolated to avoid any grounding or negative voltage issues.

Device Pinouts


RJ-45 #1 ("IN")			RJ-45 #2 ("OUT")	
Pin	Symbol	Description	Symbol	Description
1	RX+	Data Receive(+)	RX+	Data Receive(+)
2	RX-	Data Receive(-)	RX-	Data Receive(-)
3	TX+	Data Transmit(+)	TX+	Data Transmit(+)
4	+Vdc	DC power(+)	+Vdc	DC power(+)
5	+Vdc	DC power(+)	+Vdc	DC power(+)
6	TX-	Data Transmit(-)	TX-	Data Transmit(-)
7	-Vdc	DC power(-)	-Vdc	DC power(-)
8	-Vdc	DC power(-)	-Vdc	DC power(-)

Specifications

	TP-DCDC-1248DX2-HP	TP-DCDC-2448DX2-HP	TP-POE-HP-48DX2
Input Voltage	+/- 10VDC to 16VDC	+/- 18VDC to 36VDC	90-264VAC 47-63hz
Input Connector	Screw Type Compression Wire Terminal (12 AWG Max)		IEC C13 (incl. Power Cord)
POE Specification	Active PoE 802.3af/at (Mode B, 2 Pair)		
Output Voltage (+/-2.5%)	56VDC		
Data in & Data/POE Output Connector	RJ45 (Shielded)		
Output Current (max)	0.38A X 2	0.63A X 2	0.45A X 2
Output Power (total)	42W	70W	50W
Self-Consumption Power	2W		
Efficiency (min)	80%		
Line Regulation, Ripple, Noise	1%		
Load Regulation	5%		
Surge Protection	IEC61000-4-2 (ESD) ±15kV (air), ±8kV (contact) IEC61000-4-4 (EFT) 40A (5/50ns) IEC61000-4-5 (Lightning) 20A (8/20µs)		
EMC Standards	FCC Class A EN55022 Class A		
Safety Standards	UL1950, CSA 22.2 & TUV EN60950		
Operating Temperature	-40 to +70°C (-40 to +158°F)		-25 to +50°C (-13 to 122°F)
Operating Humidity (RH)	5% - 90%		
Storage Temperature	-40 to +80°C (-40 to +176°F)		
Dimensions (LxWxH)	125 x 75 x 38mm (4.9 x 3 x 1.5")		
Weight	255g (9oz)		
Warranty	1 Year		

LED Functions

Port 1 is connector labelled "IN"
Port 2 is connector labelled "OUT"
LED will light when port is powered

**DC Input Connector**

FG		Frame Ground Do Not connect to VIN-
VIN-		DC (-) Voltage In
VIN+		DC (+) Voltage In Isolated Input #1
VIN+		DC (+) Voltage In Isolated Input #2

System Ordering:**TP-DCDC-1248DX2-HP**

+/- 10-15VDC IN 56VDC POE OUT, 42W DC to DC Converter with Dual 802.3at PoE outputs

TP-DCDC-2448DX2-HP

+/- 18-36VDC IN 56VDC POE OUT, 70W DC to DC Converter with Dual 802.3at PoE outputs

TP-POE-HP-48DX2

110/220VAC IN 56VDC POE OUT, 50W PoE Injector with Dual 802.3at PoE outputs

For further information contact:Tyconpower.com

TYCON Power
Systems
14641 S 800 W Suite A
Bluffdale, UT 84065
PH: 801-432-0003
FAX: 801-618-4220