



# Passive POE to 802.3af/at Converter =

### **Features**

- Converts 24VDC Passive POE to 56VDC 802.3af/at 35W POE Output
- Run 802.3af/at equipment from 24VDC Passive POE switches like Tycon TP-SW5G-NC / TP-SW8-NC or Ubiquiti TOUGHSwitch™
- POE output up to 35W
- Remotely Power Equipment thru CAT5/6 Cable up to 100m
- Short Circuit, Over Current and Over Voltage Protection

## **Applications**

- Wireless Access Points and Client Devices
- IP Phone and Security Camera Systems

## Description

The **TP-POE-2456D** is a unique Power Over Ethernet adapter which converts a 24VDC passive POE input to an 802.3af/at 56VDC POE output. The only connections required are CAT5/6 cables. The IEEE 802.3af/at compliant POE output is capable of up to 35W power output. The POE input is 22V to 36VDC passive POE so the TP-POE-2456D is perfect for running IP POE Cameras or other POE devices from passive POE switches like the Tycon TP-SW5G-NC / TP-SW8-NC or Ubiquiti TOUGHSwitch<sup>™</sup>.

The units supply power to the remote device on the unused Ethernet pins 4,5(V+) and 7,8(V-). The Ethernet spec supports distances up to 100m (328 feet).

They have various protections for surge, short circuit, overload and overvoltage.

## **Device Pinouts**

RJ-45 Input (Data Only)			RJ-45 Output (Data & Power)	
Pin	Symbol	Description	Symbol	Description
1	RX+	Data Receive(+)	RX+	Data Receive(+)
2	RX-	Data Receive(-)	RX-	Data Receive(-)
3	TX+	Data Transmit(+)	TX+	Data Transmit(+)
4	NC	No Connection	+Vdc	DC power(+)
5	NC	No Connection	+Vdc	DC power(+)
6	TX-	Data Transmit(-)	TX-	Data Transmit(-)
7	NC	No Connection	-Vdc	DC power(-)
8	NC	No Connection	-Vdc	DC power(-)



TP-POE-2456D Passive POE to 802.3af/at POE Converter

## **TP-POE-2456D**

#### Page 2

## **Specifications**

	TP-POE-2456D	
Passive POE Input Voltage	22VDC to 36VDC	
<b>Output Overvoltage Protection</b>	58V	
POE Output	56VDC 802.3af and 802.3at compatible	
Output Current	0.625A @ 56V	
Output Power	35W Max	
Load Regulation	5%	
Ripple / Noise	2%	
Operating Temperature	-30 to +60°C (-22 to +140°F)	
Operating Humidity (RH)	5% - 90%	
Storage Temperature	-40 to +80°C (-40 to +176°F)	
Dimensions (LxWxH)	85 x 76 x 36mm (3.4 x 3 x 1.4")	
Weight	150g (5.3oz)	

Notes:

- All shipments F.O.B. Bluffdale, UT 84065
- Tycon Power Systems Power Sources carry a 1 year warranty

#### System Ordering:

TP-POE-2456D 24VDC Passive POE to 802.3af/at POE 35W Converter

### For further information contact:

Tyconpower.com



FAX: 801-618-4220