



HARDWARE SPECS

SOFTWARE SPECS

PACKAGE CONTENTS

▶ TS-351-4G



CPU	Intel® Celeron® J1800 dual-core 2.41 GHz processor (burst up to 2.58 GHz)
-----	---

CPU Architecture	64-bit x86
------------------	------------

Graphic Processors	Intel® HD Graphics
--------------------	--------------------

[Pre-Sales Online Chat](#)

[NAS Selector](#)

Floating Point Unit



Hardware-accelerated
Transcoding

✓, up to 1080P

System Memory

4 GB SODIMM DDR3L (1 x 4 GB)

Maximum Memory

8 GB (2 x 4 GB)

Memory Slot

2 x SO-DIMM DDR3L

When installing two memory modules, please ensure that they are the same size and ideally use the same type of RAM for both memory slots.

Flash Memory

512MB (Dual boot OS protection)

[Pre-Sales Online Chat](#)

[NAS Selector](#)

Drive Bay

3 x 3.5-inch SATA 6Gb/s, 3Gb/s

Bay 1, 2: SATA 3Gbps

Bay 3: SATA 6Gbps

Drive Compatibility

3.5-inch SATA hard disk drives

2.5-inch SATA hard disk drives

2.5-inch SATA solid state drives

A 2.5" drive tray base is needed to install a 2.5" SSD/HDD

Hot-swappable



M.2 SSD Slot

2 x M.2 2280 NVMe 500 MB/s slots

SSD Cache Acceleration Support

Drive bay 3
M.2 Slots 1 to 2

[Pre-Sales Online Chat](#)

[NAS Selector](#)

Gigabit Ethernet Port (RJ45) 1

Jumbo Frame 

USB 2.0 port 2

USB 3.0 port 1

HDMI Output 1, HDMI 1.4a (up to 1080p)

Audio Output 1 x built-in speaker, 1 x 3.5mm line out jack (for amplifiers or speakers)

Form Factor

Tower

LED Indicators

System Status, LAN, USB, HDD1~3, M.2 SSD1~2

Buttons

Power, Reset, USB Copy

Dimensions (HxWxD)

5.59 × 5.91 × 10.24 inch

Weight (Net)

3.62 lbs

Weight (Gross)

5.93 lbs

[Pre-Sales Online Chat](#)

[NAS Selector](#)

Operating temperature 0 - 40 °C (32°F - 104°F)

Relative Humidity 5-95% RH non-condensing, wet bulb: 27 °C (80.6 °F)

Power Supply Unit 65W adapter, 100 - 240V

Power Consumption: HDD 18.56 W
Sleep Mode

Power Consumption: Operating 26.22 W
Mode, Typical

With drives fully populated

Fan 1 x 90mm, 12VDC

[Pre-Sales Online Chat](#)

[NAS Selector](#)

Sound Level

21.8 db(A)

System Warning

Voice prompts or Buzzer

Kensington Security Slot



Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.

 [Where to Buy](#)

 [Download Center](#)

 [App Center](#)

 [Subscribe](#)

