



- HARDWARE SPECS
- SOFTWARE SPECS
- PACKAGE CONTENTS

▶ **TS-863XU-4G**



CPU AMD G-Series GX-420MC quad-core 2.0 GHz processor

CPU Architecture 64-bit x86

Floating Point Unit

Encryption Engine

✓ (AES-NI)

System Memory

4 GB SO-DIMM DDR3L (1 x 4 GB)

Maximum Memory

16 GB (2 x 8 GB)

Memory Slot

2 x SO-DIMM DDR3L

For dual-DIMM configurations, you must use a pair of identical DDR3 RAM modules.

Flash Memory

512 MB (Dual boot OS protection)

[Pre-Sales Online Chat](#)

[NAS Selector](#)

Drive Bay

8 x 3.5-inch SATA 6Gb/s, 3Gb/s

The system is shipped without HDD.
For the HDD compatibility list, please visit
<https://www.qnap.com/compatibility/>

Drive Compatibility

3.5-inch SATA hard disk drives
2.5-inch SATA hard disk drives
2.5-inch SATA solid state drives

Hot-swappable



M.2 SSD Slot

Optional via a PCIe adapter

SSD Cache Acceleration Support



[Pre-Sales Online Chat](#)

[NAS Selector](#)

Gigabit Ethernet Port (RJ45)

4

Expandable with an optional PCIe adapter

10 Gigabit Ethernet Port

1 x 10GBASE-T (10G/5G/2.5G/1G/100M)

Pre-installed with a PCIe adapter

Jumbo Frame



PCIe Slot

1

Slot 1: PCIe Gen 2 x4

Pre-installed with the QXG-10G1T 10GbE adapter

USB 2.0 port

-

[Pre-Sales Online Chat](#)

[NAS Selector](#)

USB 3.0 port 2

USB 3.1 Gen 2 (10Gbps) Port Optional via a PCIe adapter

Form Factor 2U Rackmount

LED Indicators HDD 1-8, Status, LAN, USB, Power

Buttons Power, Reset

Dimensions (HxWxD) 3.5 × 18.98 × 21.02 inch

[Pre-Sales Online Chat](#)

[NAS Selector](#)

Weight (Net) 24.29 lbs

Operating temperature 0 - 40 °C (32°F - 104°F)

Relative Humidity 5-95% RH non-condensing, wet bulb: 27 °C (80.6 °F)

Power Supply Unit 250W, Input: 110-240 Vac~, 50-60Hz, 5A

Power Consumption: HDD
Sleep Mode 40.28 W

Power Consumption: Operating
Mode, Typical 94.4 W

Sound Level

35 db(A)


System Warning

Buzzer

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.

 [Where to Buy](#)

 [Download Center](#)

 [App Center](#)

 [Subscribe](#)

