



- HARDWARE SPECS
- SOFTWARE SPECS
- PACKAGE CONTENTS

▶ **TVS-472XT-PT-4G**

CPU Intel® Pentium G5400T 2-core 3.1 GHz Processor

CPU Architecture 64-bit x86

Graphic Processors Intel® UHD Graphics 610

---

Floating Point Unit



---

Encryption Engine

✓ (AES-NI)

---

Hardware-accelerated  
Transcoding



---

System Memory

4 GB SODIMM DDR4 (2 x 2 GB)

---

Maximum Memory

32 GB ( 2 x 16 GB)

---

Memory Slot

2 x SO-DIMM DDR4

---

[Pre-Sales Online Chat](#)

[NAS Selector](#)

---

Flash Memory 5GB (Dual boot OS protection)

---

Drive Bay 4 x 3.5-inch SATA 6Gb/s, 3Gb/s

---

Drive Compatibility 3.5-inch bays:  
3.5-inch SATA hard disk drives  
2.5-inch SATA hard disk drives  
2.5-inch SATA solid state drives


---

Hot-swappable 

---

M.2 SSD Slot 2 x M.2 2280 PCIe Gen3 x2 slots

---

SSD Cache Acceleration Support 

---

[Pre-Sales Online Chat](#)

[NAS Selector](#)

---

---

Gigabit Ethernet Port (RJ45) 2

---

10 Gigabit Ethernet Port 1 x 10GBASE-T (10G/5G/2.5G/1G/100M)

---

Jumbo Frame 

---

Thunderbolt Port 2 (Thunderbolt™ 3)

---

PCIe Slot 2  
Slot 1: PCIe Gen 3 x16 (CPU)  
Slot 2: PCIe Gen 3 x4 (PCH)

Slot 1 is preinstalled with a Thunderbolt 3 adapter

---

USB 3.0 port

[Pre-Sales Online Chat](#)

[NAS Selector](#)

---

---

USB 3.1 Gen 2 (10Gbps) Port

2 x Type-C USB 3.1 Gen2 5V/3A 10Gbps  
2 x Type-A USB 3.1 Gen2 5V/1A 10Gbps

---

IR Sensor

✓ (QNAP RM-IR004 & MCE)

---

HDMI Output

1, HDMI 2.0 (up to 3840 x 2160 @ 60Hz)

---

Audio Input

1 x 3.5mm microphone input jacks

---

Audio Output

1 x built-in speaker, 1 x 3.5mm line out jack (for amplifiers or speakers)

---

Form Factor

Tower

---

[Pre-Sales Online Chat](#)

[NAS Selector](#)

---

LED Indicators

HDD 1-4, Status, LAN, USB port, M.2 port

---

LCD Display/ Button



Buttons

Power, Reset, USB Copy

---

Dimensions (HxWxD)

7.41 × 7.85 × 11.01 inch

---

Weight (Net)

11.9 lbs

---

Weight (Gross)

15.45 lbs

---

[Pre-Sales Online Chat](#)

[NAS Selector](#)

---

Operating temperature 0 - 40 °C (32°F - 104°F)

---

Relative Humidity 5-95% RH non-condensing, wet bulb: 27 °C (80.6 °F)

---

Power Supply Unit 250W, 100-240V

---

Power Consumption: HDD Sleep Mode 24.14 W

---

Power Consumption: Operating Mode, Typical 37.32 W

With WD10EFRX drives fully populated

---

Fan System fan: 1 x 120mm, 12VDC  
CPU fan: 2 x 60mm ball bearing

[Pre-Sales Online Chat](#)

[NAS Selector](#)

---

---

Sound Level

21.2 db(A)

---

System Warning

Voice prompts or Buzzer

---

Kensington Security Slot



---

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

\* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.

 [Where to Buy](#)

 [Download Center](#)

 [App Center](#)

 [Subscribe](#)

