

VMGB-605

4MP Face Recognition Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 4x Zoom Lens



- Face Recognition
- 4 Megapixel
- Day & Night with Superior Low Light Sensitivity and Adaptive IR LED
- Extreme WDR
- Event trigger, response and notification

► Specifications

Device

Product Type	Zoom Dome
Maximum Resolution	4MP
Product Application	Face Recognition
Application Environment	Indoor
Image Sensor	Progressive Scan CMOS
Sensor Size	1/1.8 "
Day / Night	Yes
Low Light Sensitivity	Superior
Minimum Illumination	Color: 0.0005 lux at F1.2 (AGC on); B/W: 0.0001 lux at F1.2 (AGC on); B/W: 0 lux (IR LED on)
Mechanical IR Cut Filter	Yes
IR LED	Adaptive IR LED (850 nm)
IR Working Distance	50m
Electronic Shutter	1-1/100000 second (auto mode)

Lens

Focal Length	Zoom, f8.0-32mm
Aperture	F1.7-F1.73

Zoom Ratio	4x optical zoom
Iris	P-Iris
Focus	Auto focus
Horizontal Viewing Angle	42.5° - 15.1°
Vertical Viewing Angle	23.3° - 8.64°
Viewing Angle Adjustment	Pan: 0°-355°, Tilt: 0°-75°, Rotation: 0°-355°

Video

Compression	H.265, H.264 (Baseline/ Main/ High profile), MJPEG
Maximum Frame Rate vs. Resolution	60 fps at 2560 x 1440 60 fps at 1920 x 1080 60 fps at 1280 x 720 30 fps at 704 x 480 30 fps at 640 x 480
Multi-Streaming	Simultaneous 5 streams
Wide Dynamic Range	Extreme WDR (140 dB)
Image Enhancement	White Balance, Saturation, Brightness, Contrast, Sharpness, Automatic gain control, Backlight compensation (BLC), Defogging, Digital Image Stabilizer (DIS, EIS)
Digital Noise Reduction	3D DNR
Privacy Mask	Yes
Built-in Analytics	Face Detection, People Detection, Vehicle Detection, Tampering Detection, People Line Crossing Detection, People Enter Area Detection, People Exit Area Detection, People Intrusion Detection, Vehicle Line Crossing Detection, Vehicle Enter Area Detection, Vehicle Exit Area Detection, Vehicle Intrusion Detection, Face Recognition

Audio

Audio Type	2-way, Built-in Microphone, Stereo Line-in, Line-out
Audio Compression	G.711, G.722.1, G.726, PCM, MP2L2, AAC, MP3

Network

Network Protocol & Service	IPv4/v6, TCP, UDP, PPPoE, HTTP, HTTPS, DNS, DDNS, NTP, RTP, RTSP, RTCP, SMTP, FTP, SFTP, IGMP, ICMP, ARP, UPnP, Bonjour, QoS, SNMP, TLS 1.2, IEEE 802.1X
Ethernet Port	1 x Ethernet (10/100/1000 Base-T), RJ-45 connector
Security	IP address filtering, HTTPS encryption, Password protected user level, IEEE 802.1X network access control

Video Analytics

Analysis Source Type	Video
Maximum detectable number of face or person	30 faces per frame (Recommendation)
Face Rotation	±60° (horizontal), ±30° (vertical)

Detection Range

Observation Range	Detection: 150.3m-400m Recognition: 30.1m-80m Identification: 15m-40m
-------------------	---

Event

Event Trigger	Video motion detection, External device through digital input, Sound detection, Intelligent event detection, Disk full, Disk not found
---------------	--

Event Response

Send E-mail Notification, Save video to local storage, Upload snapshot to FTP server, Activate external device through digital output

System

Language

Multi-Language, English, Traditional Chinese

Integration

ONVIF Compliant

Yes, Profile S, Profile G, Profile T

Storage

User Database

Face Picture Capacity: 150,000

Interface

Serial Port

1 x RS-485

Audio Interface

Built-in microphone, 1/1, 3.5mm Phone Jack

Analog Video Output

1 x CVBS, Composite output, for installation only

Local Storage

MicroSD, MicroSDHC, MicroSDXC Memory Card Slot (bundled 64GB SD card; support for up to 256GB)

Digital Input/Output

1/1

Operating Button

Reset Button

General

Power Source

DC 12V, AC 24V, PoE Class 4 (IEEE802.3at)

Power Consumption

12.4 W (DC), 12.5 W (PoE)

Dimensions

(Ø x L): 140.5mm x 122.6mm (5.5" x 4.8")

Environmental Casing

Vandal proof (IK10)

Operating Temperature

-30°C ~ 60°C (-22°F ~ 140°F)

Real-time Clock (RTC)

Yes

Warranty

3 Year(s). For extended warranty offering, see <http://www.acti.com/support/warranty>

► Related Products

Bullet - Zoom Bullet

VMGB-410



2MP ALPR Metadata Camera with 4.3x Zoom lens, f2.8-12mm/F1.2-2.5 (HOV:114.5°-41.8°), P-Iris, H.265/H.264, 3D DNR, MicroSD/MicroSDHC/MicroSDXC, PoE/DC12V, IP67, IK10 (metal casing), DI/DO, Built-in Analytics

Metadata Generator Device - Metadata Camera

VMGB-370



4MP Metadata Camera with Day/Night, IR LED, Built-in Human Temperature Detection

VMGB-400



2MP ALPR Metadata Camera with D/N, IR, Extreme WDR, SLLS, 4.3x Zoom lens, f2.8-12mm/F1.2-2.5 (HOV:103.3°-38.6°), H.265/H.264, 3D DNR, MicroSDHC/MicroSDXC, PoE/DC12V, IP67, IK10 (metal casing), DI/DO, RS-485, Built-in Analytics. Supported Territory: Taiwan.

Power Supply Accessories - Power Adapter

PPBX-0015



Power Adapter AC 100~240V (12V/2A Output), with universal connectors for R21CF-xx

