# **ZNR-220P**



# 16-Channel Desktop Standalone NVR with 16-port PoE Connectors 12MP

- 2-bay Desktop Standalone NVR
- Maximum Number of Video Devices: 16
- Free License: 16
- Built-in PoE Connectors (16 ports)
- Video export formats: MP4
- Web Client

# Specifications

#### **Device**

Product Type	Standalone NVR
Maximum Resolution	12MP
Maximum Number of Video devices	16
Maximum Number of Clients	Local: 1, Remote: 2
Hardware	
CPU	Hi3536
License	
License required	No
Free License	16
Live View	
Display Layout Mode	1, 4, 6, 8, 9, 16
Digital Zoom	Yes
Event Status	Display event status upon alarm or upon connection loss or recovery between server and client
Instant playback	Instant Playback in live view window
PTZ	
PTZ Control	PTZ Control, Speed Control

www.acti.com

\/	$\sim$	$\sim$
v	ıu	u

Compression	H.265, H.264
Maximum Frame Rate vs. Resolution	20 fps at 4072 x 3076 30 fps at 3840 x 2160 20 fps at 2688 x 1520 25 fps at 1920 x 1080 25 fps at 1280 x 720
Accello	

#### **Audio**

Audio Type	2-way, Line-in, Line-out	
------------	--------------------------	--

#### **Network**

Ethernet Port Total ports: 17 port(s) Non-PoE: 1 port(s), Ethernet (10/100/1000 Base-T), RJ-45 connector PoE: 16 port(s),	Ethernet
---	----------

# Recording

Scheduled Recording	Yes
Event Recording	Yes
Manual Recording	Yes
Maximum Recording Throughput	160 Mbps

# Search & Playback

Playback Control	Continuous forward and backward playback with speeds 1/8x, 1/4x, 1/2x, 1x, 2x, 4x, 8x, 16x, 32x, 64x, 128x, 256x, pause, stop
Synchronized Playback	16 channels
Video Export	MP4

## **System**

Permission control	128 Remote users, Customizable permissions for user groups
Client PC Operating System	Windows 8, Windows 7
Server Operating System	Embedded Linux
USB	1-Port USB 2.0, 1-Port USB 3.0

#### Integration

ONVIF Compliant	Yes
Web Browser	IE 10 or newer

# Storage

Storage Bay	SATA, Max. 2 Disk(s)
Maximum Recording Capacity	8TB x2
RAID Level	No

### Interface

Digital Input/Output	4/1
Local Access	HDMI/VGA monitor, USB keyboard & mouse

## General

PoE Output	Maximum 30 Watts per port
PoE Power Budget	Maximum 240 W
Power Source	AC 100-240V


#### Standalone NVR

Power Consumption	20 W (AC)
Weight	2480g (5.47lb)
Dimensions	(W x H x D): 380mm x 315mm x 46mm (15" x 12.4" x 1.8")
Operating Temperature	10°C ~ 55°C (14°F ~ 131°F)
Operating Humidity	10% - 90% RH
Remote Access	Web Client
Approvals	CE, FCC
Warranty	2 Year(s)

# **▶** Related Products

## **Mounting Accessories - Standalone NVR Mount**

PMAX-1204



Note: Some mounting accessories may need additional accessories for installation. Please check <a href="www.acti.com/mountingselector">www.acti.com/mountingselector</a> for more information.